

DEL MORINO – Bio Shredder

BiOnda

Bio Shredder

Ø MAX cm 5 / 6 - inch 2



This bio shredder is suitable for semi- professional use. The quality/price ratio is one of the best in its field.


STANDARD FEATURES

- 1ST QUALITY STEEL FRAME, HIGH STRENGTH, THICKNESS 4 MM LASER CUT, MACHINE BENT AND WELDED BY ROBOT
- BELT DRIVE WITH TENSIONER
- ROTOR BALANCED ELECTRONICALLY, FORCED VENTILATION, STEEL BEARING SUPPORTS, HIGHLY RESISTANT STEEL SHAFT
- 6 SWINGING REVERSIBLE HAMMERS AND ONE BLADE OF HIGH RESISTANCE TEMPERED STEEL WITH QUICK REPLACEMENT SYSTEM
- ADJUSTABLE COUNTER BLADE, EASILY REPLACEABLE
- SELF-CLEANING SCREEN WITH LONGITUDINAL SLOTS AND QUICK REMOVAL SYSTEM
- TUBELESS TIRES Ø 200 MM WITH STEEL RIMS AND RUBBER TREAD

Model	version	hp	kW	cm Ø	in Ø	n.	n.	kg	lbs	Pricing
BIONDA	Honda GP 160	5,5	-	5	2"	1	6	78	172	2,302.00

DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
Bionda	90	55	105



PACKAGING

Box + Pallet \$73.00



Pugio

Bio Shredder

Ø MAX cm 5 / 6 - inch 2



This bio shredder is suitable for semi-professional use.



STANDARD FEATURES

- 1ST QUALITY STEEL FRAME, HIGHLY RESISTANT, ANTI VIBRATION, THICKNESS 5 MM LASER CUT, MACHINE BENT AND WELDED BY ROBOT
- BELT DRIVE (SECTION B) WITH TENSIONER
- ROTOR: FORCES VENTILATION, STEEL BEARING SUPPORTS, HIGHLY RESISTANT STEEL SHAFT
- 6 SWINGING REVERSIBLE HAMMERS AND ONE BLADE OF HIGH RESISTANCE TEMPERED STEEL WITH QUICK REPLACEMENT SYSTEM, BALANCED ELECTRONICALLY
- ADJUSTABLE COUNTER BLADE, EASILY REPLACEABLE
- SELF-CLEANING SCREEN WITH LONGITUDINAL SLOTS AND QUICK REMOVAL SYSTEM
- TUBELESS TIRES 210 MM DIAMETER WITH STEEL RIMS AND RUBBER TREAD
- PTO VERSION, CATEGORY 1 CARDAN SHAFT - 700 MM
- ENGINE VERSION: IT CAN BE SUPPLIED WITH HONDA GP160 OR GP200 ENGINE



Model	version	hp	cm	in	n.	n.	kg	lbs	Pricing
PUGIO GP 160	Honda GP 160	5,5	5 - 6	1,6-2"	1	6	90	198	2,571.00
PUGIO GP 200	Honda GP 200	6,5	5 - 6	1,6-2"	1	6	97	214	2,636.00
PUGIO 3P	Tractor PTO 3P	10 - 30	5 - 6	1,6-2"	1	6	97	214	2,478.00

Model	OPTIONAL	Pricing
-------	----------	---------




T

3 point hitch for tractor PTO

846.00

DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
Pugio	90	72	105



PACKAGING

Box + Pallet \$73.00



DEL MORINO – Bio Shredder



Vulcan

Bio Shredder

Ø MAX cm 5 - 6 - inch 2



Bio shredder designed for semi-professional use. It guarantees reliable and efficient operation.



STANDARD FEATURES

- 1ST QUALITY STEEL FRAME, HIGH RESISTANT, ANTI VIBRATION, THICKNESS 5 MM LASER CUT, MACHINE BENT AND WELDED BY ROBOT
- BELT DRIVE (SECTION B) WITH TENSIONER
- ROTOR: FORCES VENTILATION, STEEL BEARING SUPPORTS, HIGHLY RESISTANT STEEL SHAFT
- 6 SWINGING REVERSIBLE HAMMERS AND TWO BLADES OF HIGH RESISTANCE TEMPERED STEEL WITH QUICK REPLACEMENT SYSTEM, BALANCED ELECTRONICALLY
- ADJUSTABLE COUNTER BLADE, EASILY REPLACEABLE
- SELF-CLEANING SCREEN WITH LONGITUDINAL SLOTS AND QUICK REMOVAL SYSTEM
- TUBELESS TIRES 210 MM DIAMETER WITH STEEL RIMS AND RUBBER TREAD
- PTO VERSION, CATEGORY 1 CARDAN SHAFT - 700 MM
- ENGINE VERSION: IT CAN BE SUPPLIED WITH HONDA GP200 OR GX270 ENGINE

Model	version	hp	cm	in	n.	n.	kg	lbs	Pricing
VULCAN GP 200	Honda GP 200	6,5	5 - 6	1,6 - 2"	2	6	109	240	3,444.00
VULCAN 3P	Tractor PTO 3P	10 - 30	5 - 6	1,6 - 2"	2	6	122	269	2,991.00

Model	OPTIONAL	Pricing
-------	----------	---------




T

3 point hitch for tractor PTO

846.00

DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
Vulcan	90	55	105



PACKAGING

Box + Pallet \$73.00



DEL MORINO – Bio Shredder



Scutum

Bio Shredder

Ø MAX cm 7 - 9 - inch 3



This bio shredder is both reliable and safe. It surpassed all the tests to assure the safety of the operator and assure the shredding performance with top marks.

STANDARD FEATURES

- 1ST QUALITY STEEL FRAME, HIGH STRENGTH, ANTI VIBRATION, THICKNESS 5 MM LASER CUT, MACHINE BENT AND WELDED BY ROBOT
- "V" BELT TRANSMISSION SECTION B WITH TENSIONER
- ROTOR: FORCED VENTILATION, STEEL BEARING SUPPORTS, HIGHLY RESISTANT STEEL SHAFT
- 6 SWINGING REVERSIBLE HAMMERS AND 2 BLADES OF HIGHLY RESISTANT TEMPERED STEEL WITH QUICK REPLACEMENT SYSTEM, BALANCED ELECTRONICALLY
- 2 ADJUSTABLE COUNTER BLADES, EASILY REPLACEABLE.
- SELF CLEANING SCREEN WITH LONGITUDINAL SLOTS AND QUICK REMOVAL SYSTEM
- PNEUMATIC TIRES 330 MM DIAMETER
- PTO VERSION WITH CATEGORY 1, UNIVERSAL PTO SHAFT - 700 MM
- ENGINE VERSION: IT CAN BE SUPPLIED WITH HONDA GX270 OR GX390 ENGINE



Model	version	hp	cm	in	n.	n.	kg	lbs	Pricing
SCUTUM GX 270	Honda GX 270	9	7 - 9	3"	2	6	145	320	4,015.00
SCUTUM GX 390	Honda GX 390	13	7 - 9	3"	2	6	150	331	4,357.00
SCUTUM 3P	Tractor PTO 3P	10 - 45	7 - 9	3"	2	6	150	331	3,241.00

Model	OPTIONAL	Pricing
-------	----------	---------



T

3 point hitch for tractor PTO

902.00

Model	Pricing
-------	---------




KP

Extension of ejection tube 1,80 m

171.00

DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
Scutum	110	55	120



PACKAGING

Box + Pallet **\$73.00**



DEL MORINO – Bio Shredder



Argo

Bio Shredder

Ø MAX cm 10 - inch 4



A professional chipper/shredder with gravity-feed and high-level discharge. Reliability and safety are key elements of this machine.




STANDARD FEATURES

- HIGHLY RESISTANT STEEL FRAME, CUT, BENT AND WELDED BY ROBOT
- V BELT TRANSMISSION WITH 2 BELTS (SECTION B) WITH SCREW TENSIONER
- 3 POINT HITCH, CATEGORY 4 PTO SHAFT
- 4 REVERSIBLE CHIPPING BLADES OF HIGH RESISTANCE STEEL MOUNTED ON A VENTILATED DISC.
- QUICK ACCESS TO THE ROTOR FOR EASY BLADES REPLACEMENT.
- CHIPPER DISC HAS STEEL BEARING SUPPORTS AND IS ELECTRONICALLY BALANCED.
- SELF-FEED (GRAVITY) HOPPER, CHIPPING DISC PULLS BRANCHES IN AS IT CHIPS, MAX DIAMETER 110MM (4.5 INCH).
- MATERIAL DISCHARGE 1.5M (5 FOOT) HIGH AND 360° ADJUSTABLE

Model	version	hp	cm	in	n.	kg	lbs	Pricing
ARGO 3P	Tractor PTO 3P	20 - 80	10	4	4	215	474	3,836.00

DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
Argo	170	120	170



PACKAGING

Pallet \$73.00



DEL MORINO – Bio Shredder

Scorpion

Bio Shredder

Ø MAX cm 12-14 - inch 5



A professional chipper/shredder with high level discharge. A "No Stress" version is available which automatically adjusts the feed rollers to prevent the engine switching-off of the tractor. Reliability and safety are key elements of this machine.


STANDARD FEATURES

- HIGHLY RESISTANT STEEL FRAME, CUT, BENT AND WELDED BY ROBOT
- V BELT TRANSMISSION WITH 2 BELTS (SECTION B) WITH SPRING LOADED TENSIONER
- VENTILATED HOLDER DISC, STEEL BEARING SUPPORTS, ROTOR SHAFT IN HIGH RESISTANCE STEEL, DISC 35 MM THICKNESS AND 500 MM DIAMETER
- QUICK ACCESS TO BLADE HOLDER FOR EASY BLADE REPLACEMENT
- 4 REVERSIBLE BLADES OF HIGH RESISTANCE STEEL
- INDEPENDENT HYDRAULIC SYSTEM. FEED ROLLER WITH INVERSION DEVICE AND SECURITY VALVE
- 3 POINT HITCH, CATEGORY 4 PTO SHAFT - 700 MM
- DISCHARGE 2 M HIGH AND ADJUSTABLE 360°. MAX WOOD CUT DIAMETER 140 MM (5 INCH.)

Model	NO STRESS SYSTEM	hp	cm	in	n.	kg	lbs	Pricing
Scorpion	NO	20 - 60	12	5"	4	380	838	10,142.00
Scorpion NO STRESS	YES	20 - 60	12-14	5"	4	380	838	10,667.00

DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
Scorpion	180	130	145
Scorpion NS	180	130	145



PACKAGING

Pallet \$73.00

