

# DEL MORINO – Potato Digger

## DM 50

Potato digger

HP


12 - 30

kW

10 - 22

rpm




540

 cm 15 - 30 - inch 6 - 12




### STANDARD FEATURES

- 3 POINT HITCH, CATEGORY 1. DRIVE SHAFT AT 540 RPM
- 1 FIXED PLOWSHARE. OSCILLATING SIEVE SEPARATES POTATOES FROM SOIL
- ADJUSTABLE WHEELS FOR DEPTH CONTROL
- UNIVERSAL PTO SHAFT CATEGORY 1
- REAR DISCHARGE

Model	hp							Pricing
		cm	in	cm	in	kg	lbs	
DM 50	12 - 30	50	20"	90	36"	155	342	3,443.00

### DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
DM 50	140	90	100



# DEL MORINO – Potato Digger

## DM 100

Potato digger

HP

30 - 50

kW

22 - 40

rpm

540



cm 15 - 30 - inch 6 - 12



### STANDARD FEATURES


- THREE-POINT HITCH, CATEGORY 1. DRIVE SHAFT WITH FLYWHEEL, 540 RPM
- STEEL FLYWHEEL THREE INTERCHANGEABLE FURROWS
- OSCILLATING SIEVES SEPARATE POTATOES FROM SOIL
- ADJUSTABLE STEEL DISCS FOR DEPTH CONTROL
- UNIVERSAL PTO SHAFT CATEGORY 4
- SIDE DISCHARGE



Model	hp	cm	in	cm	in	kg	lbs	Pricing
DM 100	30 - 50	60	24"	150	60"	305	762	4,477.00

### DIMENSIONS

Type	A (cm)	B (cm)	C (cm)
DM 100	160	170	105



Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.

# DEL MORINO – Potato Digger

## BPO A

Potato digger with connecting bar

HP

12 - 30

kW

10 - 22



### STANDARD FEATURES

- COMPLETELY WELDED STEEL FRAME
- ELEMENTS: LASER CUT AND AUTOMATIC BENDING MACHINES WITH CNC CONTROL
- 2 OR 3 ELEMENTS WITH RELATED FLANGES; HIGHLY RESISTANT TEMPERED STEEL
- CATEGORY 1
- INTERCHANGEABLE ELEMENTS
- FLANGES TO ADJUST THE DISTANCE BETWEEN ELEMENTS
- ELECTROSTATIC COATING



Model		cm	in	kg	lbs	Pricing
<b>BPO A 2</b>	Bar with 2 elements	150	60	80	176	<b>842.00</b>
<b>BPO A 3</b>	Bar with 3 elements	150	60	100	220	<b>1,024.00</b>

