

9215 "*HI-DUMP"* Box

"High Capacity" and "Gentle Handling"



FEATURES:

- Combination 10 and 12 gauge steel tub construction.
- Heavy gusseted and reinforced box style frame.
- With a GVWR rating of approximately 45,000 lbs., and an empty box weight of around 15,000 lbs., the 9215 is capable of lifting and dumping approximately 30,000 lbs of product to meet the GVWR capacity.
- The variable dumping height gives you more versatility at harvest time.
- ENTIRE dumping cycle should take approximately two minutes depending on hydraulic supply output.
- The master/slave hydraulic system automatically rephases at the end of each cylinder stroke and has the flexibility to top off a truckload with a partial dump not restricted to a full dump cycle.
- Right hand dump has a 47 degree dumping angle.
- (2) 27" x 16" Sight windows and (2) tub access panels.
- Standard highway lighting.
- Adjustable height single clevis swivel hitch.
- Telescoping/adjustable length hitch pole.
- Rear Tow Bar

Models & Specifications are subject to change without prior notice.

OPTIONS:

- 18" Dumping Lip Extension
- Dual Weight Box Package
- Safety Chain

HDB9215 Specifications



Cubic Ft. Capacity Struck Level w/o Ext.	863
Cubic Ft. Capacity Struck Level w/ Ext.	1,129
Inside Length of Box	180" (15')
Inside Width of Box - Bottom/Top	65"/136" (5' 5"/11' 4")
Depth of Box	89" (7' 5")
Overall Length Min./Max w/ Pole Adjustment	304"/328" (25' 4"/27' 4")
Overall Width	158" (13' 2")
Shipping Width (top slide to hub cap)	143" (11' 11")
Loading Height	130" (10' 10")
Shipping Height	117" (9' 9")
Front Lift Cylinder (size/length)	5.5" x 72"
Rear Lift Cylinder (size/length)	4.75" x 72"
Dump Cylinders (size/length)	5" x 71.25"
Maximum Dump Lip Clearance	31" (2' 7")
Minimum Dump Height	116" (9' 8")
Maximum Dump Height	184" (15' 4")
Maximum Ground Clearance	15" (1' 3")
Tread Width	121" (10' 1")
Spindle Size	4.5"
Tire	30.5 x 32 R1 16 Ply Radial Tires
Jack	12,000 lbs.
Shipping Weight w/ Tires	15,243 lbs.



The Variable Dumping Height gives you more versatility at harvest time! The Master/Slave Elevator System has flexibility to top off a truckload with a partial dump – you are not restricted to a full dump cycle.



Item #	e Unit	List Price
HDB9215	15' HI-DUMP Wagon w/ Single Clevis Swivel Hitch	\$92,636
	OPTIONS	
TWP3032R	27" x 32" 10 Bolt Wheels w/30.5 x 32 R1 16 Ply Tires	\$14,254
HDBO18DLE	18" Dumping Lip Extension w/ 18" Front & Rear Flares	\$3,811
HDBO18DLEIC	Installation Charge for 18" Dumping Lip Extension	\$1,116
HDBO2WB	Dual Weight Box Package (Consists of 2 weight boxes w/ brackets)	\$2,195
HDBOWBW	(1) Weight Bracket for Suitcase Weights w/Hardware	\$552
HDBO10W	(10) Suitcase Weights to fit HDBOWBW Weight Brackets	\$2,625
HDBO2WBIC	Installation Charge for (2) Weight Boxes	\$182

WEIGHT BALLAST NOTE:

Loading the left tire with some type of solution ballast adds approximately 2000-2500 lbs. of weight depending on what type os solution is purchased.



Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.





Specifications

HDB9230

Cubic Ft. Capacity Struck Level w/o Ext.	(2) @863cu. ft. each
Cubic Ft. Capacity Struck Level w/ Ext.	(2) @1,129cu. ft. each
Inside Length of each Box	180" (15')
Inside Width of each Box – Bottom/Top	65"/136" (5' 5"/11' 4")
Depth of each Box	89" (7' 5")
Overall Length	568" (47′ 4″)





Overall Width	163" (13' 7")
Overall Height	158" (13' 2")
Loading Height	134" (11' 2")
Shipping Height	134" (11' 2")
Front Lift Cylinder (size/length on each box)	5.5" x 72"
Rear Lift Cylinder (size/length on each box)	4.75″ x 72″
Dump Cylinders (size/length on each box)	5" x 71.25"
Maximum Dump Lip Clearance	31" (2' 7")
Minimum Dump Height	116" (9' 8")
Maximum Dump Height	184" (15' 4")
Maximum Ground Clearance	N/A
Tread Width	163" (13' 7")
Track Pivot Shaft Size	N/A
Jack	Hydraulic
Shipping Weight	48,177 lbs.





HDB9	230T LOADMASTER 2X HI-DUMP Box	
NEWMODEL	 Combination 10 & 12-Gauge Steel Tub Construction Heavy Gusseted & Reinforced Box-Style Frame Each Box is Capable of Lifting and Dumping Approximate for a Total of 60,000# The ENTIRE Dumping Cycle Takes Approximately 2 Minury Hydraulic Supply Output) Right-Hand Dump has a 47-Degree Dumping Angle with a 15' Standard 60,000# Safety Chains Not Restricted to a Full Dump Cycle (1) 27" x 16" Sight Window and (2) Tub Access 	ites (Depending on
BASE UNIT	 Panels in each Box Overall Length 47' 4" Overall Height 13' 2" Shipping Height 11' 2" Tread Width 13' 7" Shipping Weight 48,177# Minimum Dump Height 9' 8" Maximum Dump Height 15' 4" Cubic Ft. Capacity Struck Level w/Extension (2) @ 1,129 cu. ft. each Cubic Ft. Capacity Struck Level w/o Extension (2) @ 863 cu. ft. each LED Highway Lighting w/Beacon & Work Lights Camso Track System Hydraulic Jack 	
Item #	Description	List Price
HDB9230T	Double HI-DUMP Cart with Tracks	\$278,813

HITCH OPTIONS (Required)		
HTCHB4	Category 4 Bullnose Hitch	\$833
HTCHB5	Category 5 Bullnose Hitch	\$833

HDB9230T LOADMASTER 2X HI-DUMP Box		
Item #	Description	List Price
OPTIONS (<u>NOT</u> Required)		
HDBODE36	Dumping Extension for Unloading Into a 36' Semi-Trailer <i>(Dealer Installed)</i>	\$7,165
HDBODE40	Dumping Extension for Unloading Into a 40' Semi-Trailer <i>(Dealer Installed)</i>	\$7,924



Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.