Prices Effective as of 1-24

Sub Soiler



Model SCP-33 Shown with Standard Equipment

Even though Brillion Sub Soilers are small in size, these units have the capacity to handle compaction issues just like other sophisticated units on the market, but are designed for users with minimal horsepower. Many specialty producers rely on Brillion Sub Soilers for vineyard and orchard work. The heavy-duty laser cut shank blanks with shear bolt protection make up these very basic tillage machines. One, two and three-shank models are offered.

STANDARD MACHINE SPECIFICATIONS							
Transport Height 46"	Under Frame Clearance - 29"	5" x 7" x %" Frame Structure - Single Bar Models					
Rigid Parabolic Shanks with Shear Bolt Protection	Under Frame Clearance (High Clearance) - 35"	4" x 6" x 1/4" Frame Structure - Double Bar Models					
Shear Bolt Size 5%" x 3 3/4"	2 ½" Replaceable Points	Three-Point Hitch (SCP1) - Cat. I Free Link					
Variety of Shank Spacings Available	Reversible Wearstrips	Three-Point Hitch (SCP2) - Cat. II Free Link					
Maximum of 16" Shank Working Depth	Heavy-Duty Laser Cut Shanks	Three-Point Hitch (Double Frame Models) - Cat. II Free Link					
Powder Coat Paint	Parking Stands	Three-Point Hitch (Double Frame Models) - Cat. II, IIIN Quick Coupler Hitch					
Please Note: Maximum Shank Working Depth Not To Exceed 16"							
Please Note: Maximum Horsepower Not to Exceed 40 HP per Shank							

Horsepower Requirements: 20 to 40 HP per Shank

Approximate Set-Up Time: 0.5 Hour per Shank

Pricing Information						
Model Number	Description	Working Width	Transport Width	Approximate Weight	Suggested List Price	
SCP-1	1 Shank Sub Soiler	NA	53"	227 lbs.	\$ 2,511.00	
SCP-2	2 Shank Sub Soiler	40"	53"	459 lbs.	3,825.00	
SCP-23	2 Shank Sub Soiler (Double Frame)	80"	90"	688 lbs.	4,698.00	
SCP-33	3 Shank Sub Soiler (Double Frame)	80"	90"	837 lbs.	5,555.00	
SCPH-23	2 High-Clearance Shank Sub Soiler (Double Frame)	80"	90"	708 lbs.	4,823.00	
SCPH-33	3 High-Clearance Shank Sub Soiler (Double Frame)	80"	90"	868 lbs.	5,826.00	

