

ZONE COMMANDER

Prices Effective as of 1-24



Model 2512ZCH-7 Shown with Standard Equipment

The Zone Commander is an in-line deep ripper designed for the ultimate in compaction management. The ability to open the soil surface with minimal disturbance and to fracture and loosen the soil profile to allow water and oxygen infiltration and enhanced root growth, makes the Zone Commander unique. The Zone Commander concept lays the foundation for numerous follow-up tillage practices. These models are equipped to handle heavy residue and rugged conditions with large diameter lead coulters and heavy-duty shank assemblies. Versatility is built-in with the choice of auto-reset or rigid shear bolt shank assemblies and the choice of straight leg shanks, parabolic shanks or low disturbance shanks.

STANDARD MACHINE SPECIFICATIONS		
6" x 4" Double Bar Frame Structure (3 - 5N Shanks)	Adjustable Spring Loaded Coulters:	Choice of:
6" x 6" x 1/2" Rear Frame on 2512 Models	22" Smooth Blade	1 1/4" Straight Leg Shank
6" x 4" x 1/2" Front Frame on 2512 Models	600 lbs. of Down Pressure	1 1/4" Parabolic Shank
Three-Point Hitch (3 - 5N Shanks) - Cat. II, IIIN	6" Trip Height	3/4" Low Disturbance Shank
Three-Point Hitch (5 - 9 Shanks) - Cat. III, IV	40 1/2" Under Frame Clearance	2 1/2" C.A.D.I. Point (227189) and Wearstrip (224745) on Straight Leg Shanks
Turnbuckle Adjustable Gauge Wheels:	Maximum Shank Working Depth - See Below	2 1/2" C.A.D.I. Point (227189) and Wearstrip (224747) on Parabolic Shanks
6-Bolt Wheels	Choice of:	2" V-Shaped Point (227221) and Wearstrip (224767) on Low Disturbance Shank
280/70R x 15 Radial Tires	Auto-Reset Spring Shank Assemblies	HD Pull Hitch Caddy on 10-16 Shank Models
Placement Inside Frame to Narrow Transport	HD Hydraulic Auto-Reset Shank Assemblies	385/65R x 22.5 Radial Tires on Pull Hitch Caddy
18" Total Travel	Rigid Shear Bolt Shank Assemblies	
LED Warning Lights & SMV Emblem	Powder Coat Paint	

Horsepower Requirements: 40+ HP per Shank

Approximate Set-Up Time: 1 Hour per Shank

AUTO-RESET (SPRING) MODELS - MAXIMUM SHANK WORKING DEPTH: 16"; 2,300 LBS. POINT LOAD							
Model Number	Number of Shanks/Coulters	Shank Spacing	Frame Type	Frame Extensions	Transport Width	Approximate Weight	Suggested List Price*
2511ZC-3N	3/3	30"	Narrow - Non-Folding	None	9'2"	3,538 lbs.	\$23,460.00
2511ZC-4N	4/4	30"	Narrow - Non-Folding	None	9'2"	4,245 lbs.	26,940.00
2511ZC-5N	5/5	30"	Narrow - Non-Folding	12" Bolt-On	11'8"	5,211 lbs.	32,135.00
2512ZC-5	5/5	30"	Standard - Non-Folding	None	12'5"	6,398 lbs.	33,660.00
2512ZC-6	6/6	30"	Standard - Non-Folding	12" Bolt-On	13'5"	8,209 lbs.	37,525.00
2512ZC-7	7/7	30"	Standard - Non-Folding	27" Bolt-On	15'10"	9,406 lbs.	43,765.00
2512ZCF-7	7/7	30"	Standard - Folding	24" Wing	13'11"	10,422 lbs.	53,265.00
2512ZCF-8	8/8	30"	Standard - Folding	24" Wing	16'5"	11,559 lbs.	58,320.00
2512ZCF-9	9/9	30"	Standard - Folding	24" Wing	13'11"	12,721 lbs.	63,250.00
2512ZCF-10**	10/10	30"	Standard - Folding	52" Wing	16'5"	21,686 lbs.	108,420.00
2512ZCF-11**	11/11	30"	Standard - Folding	52" Wing	18'11"	22,738 lbs.	113,465.00
2512ZCFN-11**	11/11	30"	Narrow - Folding	82" Wing	13'11"	22,738 lbs.	113,465.00
2512ZCF-12**	12/12	30"	Standard - Folding	82" Wing	16'5"	23,859 lbs.	118,520.00
2512ZCF-13**	13/13	30"	Standard - Folding	82" Wing	18'11"	24,911 lbs.	125,220.00
2512ZCF-14**	14/14	30"	Standard - Folding	82" Wing	21'5"	26,244 lbs.	130,265.00
2512ZCF-15**	15/15	30"	Standard - Folding	112" Wing	18'11"	27,113 lbs.	135,310.00
2512ZCF-16**	16/16	30"	Standard - Folding	112" Wing	21'5"	28,545 lbs.	140,375.00

* Choice of Straight Leg Shanks, Parabolic Shanks or 3/4" Low Disturbance Shanks - Please specify when placing order.

** Heavy-Duty Pull Hitch Caddy is standard equipment and is included in pricing.



Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.

Primary Tillage

ZONE COMMANDER

Prices Effective as of 1-24

Primary Tillage

Zone Commander

This is the toughest shank on the market with a massive 4,000 lb. point load to handle challenging clay soils with ease; its 28" trip height offers protection in rocky conditions.

AUTO-RESET (HD HYDRAULIC) MODELS - MAXIMUM SHANK WORKING DEPTH: 20"

Model Number	Number of Shanks/Coulters	Shank Spacing	Frame Type	Frame Extensions	Transport Width	Approximate Weight	Suggested List Price*
2512ZCH-5	5/5	30"	Standard - Non-Folding	None	12'5"	6,338 lbs.	\$ 40,500.00
2512ZCH-6	6/6	30"	Standard - Non-Folding	12" Bolt-On	13'5"	8,120 lbs.	44,445.00
2512ZCH-7	7/7	30"	Standard - Non-Folding	27" Bolt-On	15'10"	9,386 lbs.	50,785.00
2512ZCHF-7	7/7	30"	Standard - Folding	24" Wing	13'11"	10,302 lbs.	60,165.00
2512ZCHF-8	8/8	30"	Standard - Folding	24" Wing	16'5"	11,409 lbs.	64,605.00
2512ZCHF-9	9/9	30"	Standard - Folding	24" Wing	13'11"	12,541 lbs.	71,385.00
2512ZCHF-10**	10/10	30"	Standard - Folding	52" Wing	16'5"	21,476 lbs.	117,450.00
2512ZCHF-11**	11/11	30"	Standard - Folding	52" Wing	18'11"	22,540 lbs.	123,405.00
2512ZCHF-11**	11/11	30"	Narrow - Folding	82" Wing	13'11"	22,540 lbs.	123,405.00
2512ZCHF-12**	12/12	30"	Standard - Folding	82" Wing	16'5"	23,589 lbs.	129,200.00

* Choice of Straight Leg Shanks, Parabolic Shanks or 3/4" Low Disturbance Shanks - Please specify when placing order.

** Heavy-Duty Pull Hitch Caddy is standard equipment and is included in pricing.

RIGID SHEAR BOLT MODELS - MAXIMUM SHANK WORKING DEPTH: 20"

Model Number	Number of Shanks/Coulters	Shank Spacing	Frame Type	Frame Extensions	Transport Width	Approximate Weight	Suggested List Price*
2511ZCR-3N	3/3	30"	Narrow - Non-Folding	None	9'2"	2,410 lbs.	\$ 20,985.00
2511ZCR-4N	4/4	30"	Narrow - Non-Folding	None	9'2"	2,735 lbs.	22,365.00
2511ZCR-5N	5/5	30"	Narrow - Non-Folding	12" Bolt-On	11'8"	3,345 lbs.	25,695.00
2512ZCR-5	5/5	30"	Standard - Non-Folding	None	12'5"	5,573 lbs.	26,575.00
2512ZCR-6	6/6	30"	Standard - Non-Folding	12" Bolt-On	13'5"	7,219 lbs.	29,615.00
2512ZCR-7	7/7	30"	Standard - Non-Folding	27" Bolt-On	15'10"	8,251 lbs.	34,510.00
2512ZCRF-7	7/7	30"	Standard - Folding	24" Wing	13'11"	9,267 lbs.	42,520.00
2512ZCRF-8	8/8	30"	Standard - Folding	24" Wing	16'5"	10,239 lbs.	45,155.00
2512ZCRF-9	9/9	30"	Standard - Folding	24" Wing	13'11"	11,236 lbs.	50,335.00
2512ZCRF-10**	10/10	30"	Standard - Folding	52" Wing	16'5"	20,036 lbs.	94,045.00
2512ZCRF-11**	11/11	30"	Standard - Folding	52" Wing	18'11"	20,923 lbs.	97,655.00
2512ZCRF-11**	11/11	30"	Narrow - Folding	82" Wing	13'11"	20,923 lbs.	97,655.00
2512ZCRF-12**	12/12	30"	Standard - Folding	82" Wing	16'5"	21,879 lbs.	101,290.00
2512ZCRF-13**	13/13	30"	Standard - Folding	82" Wing	18'11"	22,766 lbs.	106,525.00
2512ZCRF-14**	14/14	30"	Standard - Folding	82" Wing	21'5"	23,934 lbs.	110,145.00
2512ZCRF-15**	15/15	30"	Standard - Folding	112" Wing	18'11"	24,638 lbs.	113,760.00
2512ZCRF-16**	16/16	30"	Standard - Folding	112" Wing	21'5"	25,905 lbs.	117,375.00

* Choice of Straight Leg Shanks, Parabolic Shanks or 3/4" Low Disturbance Shanks - Please specify when placing order.

** Heavy-Duty Pull Hitch Caddy is standard equipment and is included in pricing.



Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.

ZONE COMMANDER

Zone Commander

Prices Effective as of 1-24

Primary Tillage

Part Number	Description	Approximate Weight	Suggested List Price
OPTIONAL EQUIPMENT			
224460	Caddy for 5-9 Shank Units with (4) 320/70R x 15 Radials (Includes 2 Gauge Wheels on Center Frame) (Field Installation)	6,170.0 lbs.	\$ 28,915.00
	If ordered on new 5-9 Shank Units from Factory:	5,518 lbs.	ADD 25,620.00
217229	12" Off-Set Shank Mount for 2512 Auto-Reset Spring and Hydraulic or Rigid Shear Bolt Models (Factory Installed Only)	93.0 lbs.	ADD 330.00 Each
217335	Left-Hand Gauge Wheel for 10-16 Shank Folding Units w/HD Caddy	324.0 lbs.	3,750.00
217336	Right-Hand Gauge Wheel for 10-16 Shank Folding Units w/HD Caddy	324.0 lbs.	3,750.00
9K289	22" Ripple Coulter in Lieu of Smooth Coulter	22.0 lbs.	ADD 5.00 Each
179966	22" Pyramid Coulter in Lieu of Smooth Coulter	21.0 lbs.	ADD 10.00 Each
227191	2 3/8" Shark Fin C.A.D.I. Point in Lieu of Standard Point on 1 1/4" Straight Leg or Parabolic Shanks	24.0 lbs.	ADD 5.00 Each
227265	7" Wing Point w/ Cast Cap in Lieu of Standard Point on 1 1/4" Straight Leg or Parabolic Shanks	24.0 lbs.	ADD 100.00 Each
227207	7" Wing Point w/Chrome Cap in Lieu of Standard Point on 1 1/4" Straight Leg or Parabolic Shanks	23.0 lbs.	ADD 60.00 Each
227210	10" Wing Point w/Chrome Cap in Lieu of Standard Point on 1 1/4" Straight Leg or Parabolic Shanks	24.0 lbs.	ADD 130.00 Each
227272	10" Wing Point w/Cast Cap in Lieu of Standard Point on 1 1/4" Straight Leg or Parabolic Shanks	25.0 lbs.	ADD 170.00 Each
227245	7" Wing Point w/Chrome Cap in Lieu of Standard Point on 3/4" Low Disturbance Shank	21.0 lbs.	ADD 60.00 Each
9K873	Coverboard Kit for 1 1/4" Straight Leg Shank - Cannot be Used with Wearstrip	12.0 lbs.	110.00
184420	Coverboard Kit for 1 1/4" Parabolic Shank - Cannot be Used with Wearstrip; Must Also Order 191121 Spacer to Attach Point	12.0 lbs.	110.00
247321	Coverboard Kit for 3/4" Low Disturbance Shank - Cannot be Used with Wearstrip	19.0 lbs.	160.00
235967	Rear Tow Hitch with Slide and Hydraulic Tow Package - For 5, 7 and 9 Shank Models	563.0 lbs.	2,320.00
235965	Rear Tow Hitch with Slide and Hydraulic Tow Package - For 4, 6 and 8 Shank Models	352.0 lbs.	1,550.00
167297	Spare Tire and Wheel Assembly (280/70R x 15)	88.0 lbs.	650.00
211176	Spare Tire and Wheel Assembly (320/70R x 15)	95.0 lbs.	790.00
230884	Rear Jack Stand	165.0 lbs.	1,500.00
FIELD INSTALLED ACCESSORIES			
CALL	Auto-Reset Spring Clamp Assembly - LESS Shank, Point and Wearstrip	494.0 lbs.	2,800.00
CALL	Rigid Shear Bolt 3/4" Low Disturbance Shank Assembly with Point and Wearstrip	220.0 lbs.	1,660.00
CALL	Rigid Shear Bolt 1 1/4" Parabolic Shank Assembly - LESS Point and Wearstrip	220.0 lbs.	1,560.00
213211	12" Frame Extension w/Bolts (2 Required per Machine)	178.0 lbs.	600.00
213205	27" Frame Extension w/Bolts (2 Required per Machine)	240.0 lbs.	1,050.00
233874	Right-Hand, Heavy-Duty Coulter Assembly, 22" Smooth Blade	126.0 lbs.	1,275.00
233873	Left-Hand, Heavy-Duty Coulter Assembly, 22" Smooth Blade	126.0 lbs.	1,275.00
176846	22" Smooth Coulter Blade	20.0 lbs.	80.00
9K289	22" Ripple Coulter Blade	22.0 lbs.	85.00
179966	22" Pyramid Coulter Blade	22.0 lbs.	90.00
224747	C.A.D.I. Wearstrip for 1 1/4" Parabolic Shanks - Without Hardware	18.0 lbs.	125.00
227895	C.A.D.I. Wearstrip for 1 1/4" Parabolic Shanks - With Hardware and Keeper	20.0 lbs.	165.00
224767	C.A.D.I. Wearstrip for 3/4" Low Disturbance Shanks - Without Hardware	8.0 lbs.	80.00
224768	3/4" Low Disturbance Shank with Wearstrip, Keeper and Hardware	85.0 lbs.	750.00
224744	1 1/4" Straight Leg Shank and Wearstrip	110.0 lbs.	650.00

If ordering points and wearstrips for models prior to 2021, please call the Brillion Sales Office for correct part numbers.



Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.