# 2 Wheel

## HORST

### **LEADERS IN FOLLOWING**

Our industry leading No-Sway trailing ensures that our wagons follow your lead. Tapered roller bearings on the king pins and automotive style ball joints not only keep our wagons behind you they also provide years of hard working service. From field to farm Horst Wagons are built to get you there.

NOTE: The rated capacities provided are for the chassis only and rims and tires should be matched accordingly when ordered.





(with standard variable adjustment)

Take the precision work out of hooking up by freely moving the tongue into place and watch it lock into place as soon as it's in motion.



TAPERED ROLLER BEARINGS IN MAIN PIVOT POINTS

Roller bearings keep pivot points tight, ensuring no trailer sway and longlasting use.



AUTOMOTIVE BALL JOINTS

Automotive style ball joints not only keep our wagons behind you, they also provide years of hard working service.



TO



12,000 lbs







Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
11L x 15	8 Ply	15 x 8 x 6 HD	74"	\$3,630.00	\$2,508.00	\$2,056.00
225/75 R15	D Range	15 x 6 x 6	74"	\$3,606.00	\$2,422.00	\$2,056.00
12.5L x 15	12 Ply	15 x 10 x 6 HD	76"	\$4,130.00	\$2,569.00	\$2,056.00
245 R16	Used Truck*	16 x 8 x 6	74"	\$2,910.00	\$2,447.00	\$2,056.00
11L x 15	D Range / Hwy Ser.	15 x 8 x 6 HD	74"	\$4,399.00	\$2,508.00	\$2,056.00
11L x 15	F Range / Hwy Ser.	15 x 8 x 6 HD	74"	\$4,533.00	\$2,508.00	\$2,056.00
26 x 12	12 Ply	12 x 10.5 x 6	80"	\$3,569.00	N/A	\$2,056.00

Options	Price
Optional 10' reach length (wheelbase adj. 11' to 14')	\$71.00
High clearance option (6" increase )	\$610.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$586.00
Wide track (Custom Build) up to 90"	\$623.00
Single spring balancer	\$122.00
4" bolt on riser kit (other heights available)	\$586.00

 $<sup>^{\</sup>star}$ Used tires may not meet local regulations, check with your local authority before purchasing.



### **MODEL 185**



- 10 ton wagon gear
- Quick hitch tongue
- Standard reach length 11'
- Wheel Base adjustable 8' 8" 11' 2"
- Hubs 6 Bolt 6,000 LBS.

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
11L x 15	8 Ply	15 x 8 x 6 HD	76"	\$4,228.00	\$3,105.00	\$2,654.00
225/75 R15	D Range	15 x 6 x 6	76"	\$4,203.00	\$3,020.00	\$2,654.00
12.5L x 15	12 Ply	15 x 10 x 6 HD	78"	\$4,728.00	\$3,166.00	\$2,654.00
245 R16	Used Truck*	16 x 8 x 6	76"	\$3,508.00	\$3,044.00	\$2,654.00
11L x 15	D Range / Hwy Ser.	15 x 8 x 6 HD	76"	\$4,996.00	\$3,105.00	\$2,654.00
11L x 15	F Range / Hwy Ser.	15 x 8 x 6 HD	76"	\$5.131.00	\$3.105.00	\$2.654.00

Options	Price
Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'	
Add or subtract price per foot for over or under 11' (includes both reach poles)	\$41.00
High clearance option (6" increase )	\$610.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$586.00
Wide track (Custom Build) up to 90"	\$623.00
Wide track (Custom Build) over 90"	\$1,178.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
Rocking bolster	\$708.00
Rocking bolster for ammonia tank	\$708.00
4" bolt on riser kit (other heights available)	\$586.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.







Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
11L x 15	8 Ply	15 x 8 x 6 HD	72"	\$5,631.00	\$4,508.00	\$4,057.00
225/75 R15	D Range	15 x 6 x 6	72"	\$5,606.00	\$4,423.00	\$4,057.00
12.5L x 15	12 Ply	15 x 10 x 6 HD	74"	\$6,131.00	\$4,569.00	\$4,057.00
245 R16	Used Truck*	16 x 8 x 6	72"	\$4,911.00	\$4,447.00	\$4,057.00
11L x 15	F Range / Hwy Ser.	15 x 8 x 6 HD	72"	\$6,534.00	\$4,508.00	\$4,057.00

Options	Price
Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'	
Add or subtract price per foot for over or under 11' (includes both reach poles)	\$41.00
High clearance option (6" increase)	\$610.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$586.00
Wide track (Custom Build) up to 90"	\$623.00
Wide track (Custom Build) over 90"	\$1,178.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
Rocking bolster	\$708.00
Rocking bolster for ammonia tank	\$708.00
4" bolt on riser kit (other heights available)	\$586.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.





- 12 ton wagon gear
- Quick hitch tongue
- Standard reach length 11'
- Wheel Base adjustable 8' 8" 11' 2"
- Hubs 8 Bolt 6,500 LBS.

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
12.5L x 16	14 Ply	16 x 10 x 8	82"	\$5,802.00	\$3,886.00	\$3,191.00
12.5L x 15	F Range / Hwy Ser.	15 x 10 x 8 HD	82"	\$6,021.00	\$3,715.00	\$3,191.00
16.5 x 16.1	10 Ply	16.1 x W14C x 8	86"	\$7,558.00	\$4,289.00	\$3,191.00
11 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	82"	\$4,557.00	\$4,106.00	\$3,191.00
12 or 315 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	82"	\$4,923.00	\$4,106.00	\$3,191.00
305 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	82"	\$4,813.00	\$4,106.00	\$3,191.00
385 x 22.5	Used Truck*	22.5 x 11.75 x 8	88"	\$5,106.00	\$4,289.00	\$3,191.00
385 x 22.5	New Truck	22.5 x 11.75 x 8	88"	\$8,815.00	\$4,289.00	\$3,191.00
425 x 22.5	Used Truck*	22.5 x 11.75 x 8	88"	\$5,387.00	\$4,289.00	\$3,191.00
425 x 22.5	New Truck	22.5 x 11.75 x 8	88"	\$8,949.00	\$4,289.00	\$3,191.00

Options	Price
Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'	
Add or subtract price per foot for over or under 11' (includes both reach poles)	\$41.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$586.00
Wide track (Custom Build) up to 90"	\$623.00
Wide track (Custom Build) over 90"	\$1,178.00
2 wheel free backing surge brakes c/w double spring balancer (includes brake tongue)	\$2,928.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
Rocking bolster	\$708.00
Rocking bolster for ammonia tank	\$708.00
4" bolt on riser kit (other heights available)	\$586.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.









- 14 ton wagon gear
- Quick hitch tongue
- Standard reach length 11'
- Wheel Base adjustable 8' 8" 11' 2"
- Hubs 8 Stud 8,000 LBS.

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
14L x 16.1	8 Ply	16.1 x W11C x 8	89"	\$6,887.00	\$4,777.00	\$4,057.00
14L x 16.1	12 Ply	16.1 x W11C x 8	89"	\$7,461.00	\$4,777.00	\$4,057.00
16.5 x 16.1	10 Ply	16.1 x W14C x 8	89"	\$8,425.00	\$5,155.00	\$4,057.00
11 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$5,423.00	\$4,972.00	\$4,057.00
12 or 315 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$5,789.00	\$4,972.00	\$4,057.00
305 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$5,680.00	\$4,972.00	\$4,057.00
385 x 22.5	Used Truck*	22.5 x 11.75 x 8	89"	\$5,972.00	\$5,155.00	\$4,057.00
385 x 22.5	New Truck	22.5 x 11.75 x 8	89"	\$9,681.00	\$5,155.00	\$4,057.00
425 x 22.5	Used Truck*	22.5 x 11.75 x 8	89"	\$6,253.00	\$5,155.00	\$4,057.00
425 x 22.5	New Truck	22.5 x 11.75 x 8	89"	\$9,815.00	\$5,155.00	\$4,057.00
425 x 22.5	Used Truck*	22.5 x 13 x 8	86"	\$6,448.00	\$5,350.00	\$4,057.00
425 x 22.5	New Truck	22.5 x 13 x 8	86"	\$10,011.00	\$5,350.00	\$4,057.00
445 x 22.5	New Truck	22.5 x 13 x 8	86"	\$10,401.00	\$5,350.00	\$4,057.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 8	86"	\$12,182.00	\$5,350.00	\$4,057.00

Options	Price
Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'	
Add or subtract price per foot for over or under 11' (includes both reach poles)	\$41.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$586.00
Wide Track (Custom Build) up to 90"	\$623.00
Wide Track (Custom Build) over 90"	\$1,178.00
2 wheel free backing surge brakes c/w double spring balancer (includes brake tongue)	\$2,928.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$3,514.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Disc brake flanges (for future brake add on)	\$287.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
Rocking bolster	\$708.00
4" bolt on riser kit (other heights available)	\$653.00



### **MODEL 285**

### **HEAVY DUTY WAGON**



- 15 ton HD wagon gear
- Quick hitch tongue
- Rocking bolster
- Standard reach length 10'
- Wheel base adjustable 10' 7" 12' 1"
- Hubs 8 Stud 8,000 LBS.
- Disc brake flanges

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
16.5 x 16.1	10 Ply	16.1 x W14C x 8	93"	\$9,358.00	\$6,088.00	\$4,990.00
11 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$6,357.00	\$5,905.00	\$4,990.00
12 or 315 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$6,723.00	\$5,905.00	\$4,990.00
305 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$6,613.00	\$5,905.00	\$4,990.00
385 x 22.5	Used Truck*	22.5 x 11.75 x 8	89"	\$6,906.00	\$6,088.00	\$4,990.00
385 x 22.5	New Truck	22.5 x 11.75 x 8	89"	\$10,614.00	\$6,088.00	\$4,990.00
425 x 22.5	Used Truck*	22.5 x 13 x 8	86"	\$7,381.00	\$6,283.00	\$4,990.00
425 x 22.5	New Truck	22.5 x 13 x 8	86"	\$10,944.00	\$6,283.00	\$4,990.00
445 x 22.5	New Truck	22.5 x 13 x 8	86"	\$11,334.00	\$6,283.00	\$4,990.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 8	86"	\$13,115.00	\$6,283.00	\$4,990.00
560 / 45 x 22.5	16 Ply	22.5 x 16 x 8	92"	\$15,629.00	\$8,004.00	\$4,990.00

Options	Price
Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'	
Add or subtract price per foot for over or under 10' (includes both reach poles)	\$74.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$751.00
Wide Track (Custom Build) up to 90"	\$787.00
Wide Track (Custom Build) over 90"	\$1,245.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$3,514.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$653.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.







40,000 lbs



- 20 ton HD wagon gear
- Quick hitch tongue
- Standard reach length 10'
- Wheel base adjustable 10' 7" 12' 1"
- Hubs 8 Stud 12,000 LBS.
- Disc brake flanges

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
16.5 x 16.1	10 Ply	16.1 x W14C x 8	89"	\$9,821.00	\$6,552.00	\$5,454.00
19L x 16.1	12 Ply	16.1 x W16C x 8	91"	\$10,639.00	\$6,686.00	\$5,454.00
21.5 x 16.1	14 Ply	16.1 x W16C x 8	91"	\$12,066.00	\$6,686.00	\$5,454.00
425 x 22.5	Used Truck*	22.5 x 13 x 8	86"	\$7,845.00	\$6,747.00	\$5,454.00
425 x 22.5	New Truck	22.5 x 13 x 8	86"	\$11,407.00	\$6,747.00	\$5,454.00
445 x 22.5	New Truck	22.5 x 13 x 8	86"	\$11,798.00	\$6,747.00	\$5,454.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 8	86"	\$13,579.00	\$6,747.00	\$5,454.00
560 / 45 x 22.5	16 Ply	22.5 x 16 x 8	92"	\$16,092.00	\$8,467.00	\$5,454.00

Options	Price
Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'	
Add or subtract price per foot for over or under 10' (includes both reach poles)	\$74.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$751.00
Wide Track (Custom Build) up to 90"	\$787.00
Wide Track (Custom Build) over 90"	\$1,245.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$3,514.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$653.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.





- 20 ton HD wagon gear
- Quick hitch tongue
- Rocking bolster
- Standard reach length 10'
- Wheel base adjustable 10' 7" 12' 1"
- Hubs 8 Stud 12,000 LBS.
- Disc brake flanges

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
16.5 x 16.1	10 Ply	16.1 x W14C x 8	89"	\$10,364.00	\$7,095.00	\$5,997.00
19L x 16.1	12 Ply	16.1 x W16C x 8	91"	\$11,182.00	\$7,229.00	\$5,997.00
21.5 x 16.1	14 Ply	16.1 x W16C x 8	91"	\$12,609.00	\$7,229.00	\$5,997.00
425 x 22.5	Used Truck*	22.5 x 13 x 8	86"	\$8,388.00	\$7,290.00	\$5,997.00
425 x 22.5	New Truck	22.5 x 13 x 8	86"	\$11,950.00	\$7,290.00	\$5,997.00
445 x 22.5	New Truck	22.5 x 13 x 8	86"	\$12,341.00	\$7,290.00	\$5,997.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 8	86"	\$14,122.00	\$7,290.00	\$5,997.00
560 / 45 x 22.5	16 Ply	22.5 x 16 x 8	92"	\$16,635.00	\$9,010.00	\$5,997.00

Options	Price
Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'	
Add or subtract price per foot for over or under 10' (includes both reach poles)	\$74.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$751.00
Wide Track (Custom Build) up to 90"	\$787.00
Wide Track (Custom Build) over 90"	\$1,245.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$3,514.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$653.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.



## MODEL 485 HEAVY DUTY WAGON



- 24 ton HD wagon gear
- Quick hitch tongue
- Rocking bolster
- Standard reach length 10'
- Wheel base adjustable 10' 7" 12' 1"
- Hubs 10 Stud 16,000 LBS.
- Disc brake flanges

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
425 x 22.5	Used Truck*	22.5 x 13 x 10	86"	\$11,145.00	\$10,047.00	\$8,681.00
425 x 22.5	New Truck	22.5 x 13 x 10	86"	\$14,708.00	\$10,047.00	\$8,681.00
445 x 22.5	New Truck	22.5 x 13 x 10	86"	\$15,098.00	\$10,047.00	\$8,681.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 10	86"	\$16,879.00	\$10,047.00	\$8,681.00
560 / 45 x 22.5	16 Ply	22.5 x 16 x 10	92"	\$19,392.00	\$11,767.00	\$8,681.00

Options	Price
Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'	
Add or subtract price per foot for over or under 10' (includes both reach poles)	\$74.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$751.00
Wide Track (Custom Build) up to 90"	\$787.00
Wide Track (Custom Build) over 90"	\$1,245.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler	\$3,514.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$653.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.





### **SMOOTH TRAVEL ROAD FLEX WAGONS**

Ideal for high speed tractors our new line of ROAD FLEX running gear use suspension blocks to help eliminate bumps and vibrations when traveling down the road or through the field. ROAD FLEX suspension not only reduces the stress from towing heavy loads but also provides increased stability to Horst wagons. In addition Road Flex suspension provides independent four wheel suspension which eliminates the need for rocking bolsters.

NOTE: The rated capacities provided are for the chassis only and rims and tires should be matched accordingly when ordered.



#### **STANDARD FEATURES**



RETRACTABLE AUTOMATIC RELOCK TONGUE LATCH (with standard variable adjustment)

Take the precision work out of hooking up by freely moving the tongue into place and watch it lock into place as soon as its in motion.



TAPERED ROLLER BEARINGS IN MAIN PIVOT POINTS

Roller bearings keep pivot points tight, ensuring no trailer sway and long-lasting use.



AUTOMOTIVE BALL JOINTS

Automotive style ball joints not only keep our wagons behind you they also provide years of hard working service.



#### POAD FLEX

Road Flex suspension uses shock absorbing blocks to reduce the amount of bounce the wagon encounters as it's pulled down the road or across the field.



TO



0 lbs 48,000 lbs



**MODEL 185RF** 

20,000 lbs



- 10 ton wagon gear
- Road Flex Suspension
- Quick hitch tongue
- Standard reach length 11'
- Wheel Base adjustable 8'8" 11'2"
- Hubs 6 Bolt 6,000 LBS.

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
11L x 15	8 Ply	15 x 8 x 6 HD	76"	\$7,430.00	\$6,308.00	\$5,856.00
225/75 R15	D Range	15 x 6 x 6	76"	\$7,406.00	\$6,222.00	\$5,856.00
12.5L x 15	12 Ply	15 x 10 x 6 HD	78"	\$7,930.00	\$6,369.00	\$5,856.00
245 R16	Used Truck*	16 x 8 x 6	76"	\$6,710.00	\$6,247.00	\$5,856.00
11L x 15	D Range / Hwy Ser.	15 x 8 x 6 HD	76"	\$8,199.00	\$6,308.00	\$5,856.00
11L x 15	F Range / Hwy Ser.	15 x 8 x 6 HD	76"	\$8,333.00	\$6,308.00	\$5,856.00

Options	Price
Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'	
Add or subtract price per foot for over or under 11' (includes both reach poles)	\$41.00
High clearance option (6" increase)	\$610.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$586.00
Wide track (Custom Build) up to 90"	\$623.00
Wide track (Custom Build) over 90"	\$1,178.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$586.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.



## **MODEL 205RF**

SUSPENSION WAGON

**24,000 lbs** tire size determines GVWR



- 12 ton wagon gear
- Road Flex Suspension
- Quick hitch tongue
- Standard reach length 11'
- Wheel Base adjustable 8'8" 11'2"
- Hubs 8 Bolt 6,500 LBS.

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
12.5L x 16	14 Ply	16 x 10 x 8	82"	\$9,333.00	\$7,418.00	\$6,723.00
12.5L x 15	F Range / Hwy Ser.	15 x 10 x 8 HD	82"	\$9,553.00	\$7,247.00	\$6,723.00
16.5 x 16.1	10 Ply	16.1 x W14C x 8	86"	\$11,090.00	\$7,821.00	\$6,723.00
11 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	82"	\$8,089.00	\$7,638.00	\$6,723.00
12 or 315 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	82"	\$8,455.00	\$7,638.00	\$6,723.00
305 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	82"	\$8,345.00	\$7,638.00	\$6,723.00
385 x 22.5	Used Truck*	22.5 x 11.75 x 8	88"	\$8,638.00	\$7,821.00	\$6,723.00
385 x 22.5	New Truck	22.5 x 11.75 x 8	88"	\$12,347.00	\$7,821.00	\$6,723.00
425 x 22.5	Used Truck*	22.5 x 11.75 x 8	88"	\$8,919.00	\$7,821.00	\$6,723.00
425 x 22.5	New Truck	22.5 x 11.75 x 8	88"	\$12,481.00	\$7,821.00	\$6,723.00

Options	Price
Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'	
Add or subtract price per foot for over or under 11' (includes both reach poles)	\$41.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$586.00
Wide track (Custom Build) up to 90"	\$623.00
Wide track (Custom Build) over 90"	\$1,178.00
2 wheel free backing surge brakes c/w double spring balancer (includes brake tongue)	\$2,928.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$586.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.



## MODEL 285RF HEAVY DILTY SUSPENSION WAGON



- 15 ton HD wagon gear
- Road Flex Suspension
- Quick hitch tongue
- Standard reach length 10'
- Wheel base adjustable 10' 7" 12' 1"
- Hubs 8 Stud 8,000 LBS.
- Disc brake flanges

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
16.5 x 16.1	10 Ply	16.1 x W14C x 8	93"	\$13,652.00	\$10,383.00	\$9,285.00
11 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$10,651.00	\$10,200.00	\$9,285.00
12 or 315 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$11,017.00	\$10,200.00	\$9,285.00
305 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$10,907.00	\$10,200.00	\$9,285.00
385 x 22.5	Used Truck*	22.5 x 11.75 x 8	89"	\$11,200.00	\$10,383.00	\$9,285.00
385 x 22.5	New Truck	22.5 x 11.75 x 8	89"	\$14,909.00	\$10,383.00	\$9,285.00
425 x 22.5	Used Truck*	22.5 x 13 x 8	86"	\$11,676.00	\$10,578.00	\$9,285.00
425 x 22.5	New Truck	22.5 x 13 x 8	86"	\$15,238.00	\$10,578.00	\$9,285.00
445 x 22.5	New Truck	22.5 x 13 x 8	86"	\$15,629.00	\$10,578.00	\$9,285.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 8	86"	\$17,410.00	\$10,578.00	\$9,285.00
560 / 45 x 22.5	16 Ply	22.5 x 16 x 8	92"	\$19,923.00	\$12,298.00	\$9,285.00

Options	Price
Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'	
Add or subtract price per foot for over or under 10' (includes both reach poles)	\$74.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$751.00
Wide Track (Custom Build) up to 90"	\$787.00
Wide Track (Custom Build) over 90"	\$1,245.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$3,514.00
4 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$6,479.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$653.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.



## MODEL 325RF SUSPENSION WAGON



tire size determines GVWR





- 18 ton tandem wagon gear
- Road Flex Suspension
- Quick hitch tongue
- Standard reach length 11'
- Wheel base Adjustable 8' 8" 11' 2"
- Hubs 8 Stud 12,000 LBS.

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
14L x 16.1	12 Ply	16.1 x W11C x 8	89"	\$14,982.00	\$10,956.00	\$9,876.00
16.5 x 16.1	10 Ply	16.1 x W14C x 8	89"	\$16,428.00	\$11,523.00	\$9,876.00
19L x 16.1	12 Ply	16.1 x W16C x 8	91"	\$17,654.00	\$11,725.00	\$9,876.00
21.5 x 16.1	14 Ply	16.1 x W16C x 8	91"	\$19,795.00	\$11,725.00	\$9,876.00
11 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$11,926.00	\$11,249.00	\$9,876.00
12 or 315 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$12,475.00	\$11,249.00	\$9,876.00
305 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$12,310.00	\$11,249.00	\$9,876.00
385 x 22.5	Used Truck*	22.5 x 11.75 x 8	89"	\$12,749.00	\$11,523.00	\$9,876.00
385 x 22.5	New Truck	22.5 x 11.75 x 8	89"	\$18,313.00	\$11,523.00	\$9,876.00
425 x 22.5	Used Truck*	22.5 x 11.75 x 8	89"	\$13,170.00	\$11,523.00	\$9,876.00
425 x 22.5	New Truck	22.5 x 11.75 x 8	89"	\$18,514.00	\$11,523.00	\$9,876.00
425 x 22.5	Used Truck*	22.5 x 13 x 8	86"	\$13,463.00	\$11,816.00	\$9,876.00
425 x 22.5	New Truck	22.5 x 13 x 8	86"	\$18,807.00	\$11,816.00	\$9,876.00
445 x 22.5	New Truck	22.5 x 13 x 8	86"	\$19,392.00	\$11,816.00	\$9,876.00
400/55 22.5	16 Ply	22.5 x 13 x 8	86"	\$22,064.00	\$11,816.00	\$9,876.00

Options	Price
Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'	
Add or subtract price per foot for over or under 11' (includes both reach poles)	\$41.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$751.00
Wide Track (Custom Build) up to 90"	\$623.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$3,514.00
4 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$6,479.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$653.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.



## MODEL 308RF SUSPENSION WAGON



### **FEATURES**

- 20 ton double tandem wagon gear
- Road Flex Suspension
- Quick hitch tongue
- Hubs 8 Stud 12,000 LBS.
- Front Tandem has quad steering c/w bearings on king pins
- Standard reach length 11'
- Wheel Base Adjustable 12' 7" 15' 1"

(taken from the centre of the rear tandem axle to the front axle of front tandem.)

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
14L x 16.1	8 Ply	16.1 x W11C x 8	89"	\$21,521.00	\$17,300.00	\$15,860.00
14L x 16.1	12 Ply	16.1 x W11C x 8	89"	\$22,668.00	\$17,300.00	\$15,860.00
16.5 x 16.1	10 Ply	16.1 x W14C x 8	89"	\$24,596.00	\$18,056.00	\$15,860.00
19L x 16.1	12 Ply	16.1 x W16C x 8	91"	\$26,230.00	\$18,325.00	\$15,860.00
21.5 x 16.1	14 Ply	16.1 x W16C x 8	91"	\$29,085.00	\$18,325.00	\$15,860.00
11 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$18,593.00	\$17,690.00	\$15,860.00
12 or 315 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$19,325.00	\$17,690.00	\$15,860.00
305 x 22.5	Used Truck*	22.5 x 8.25 x 8 HD	89"	\$19,106.00	\$17,690.00	\$15,860.00
385 x 22.5	Used Truck*	22.5 x 11.75 x 8	89"	\$19,691.00	\$18,056.00	\$15,860.00
385 x 22.5	New Truck	22.5 x 11.75 x 8	89"	\$27,109.00	\$18,056.00	\$15,860.00
425 x 22.5	Used Truck*	22.5 x 11.75 x 8	89"	\$20,252.00	\$18,056.00	\$15,860.00
425 x 22.5	New Truck	22.5 x 11.75 x 8	89"	\$27,377.00	\$18,056.00	\$15,860.00
425 x 22.5	Used Truck*	22.5 x 13 x 8	86"	\$20,643.00	\$18,447.00	\$15,860.00
425 x 22.5	New Truck	22.5 x 13 x 8	86"	\$27,768.00	\$18,447.00	\$15,860.00
445 x 22.5	New Truck	22.5 x 13 x 8	86"	\$28,548.00	\$18,447.00	\$15,860.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 8	86"	\$32,111.00	\$18,447.00	\$15,860.00

Options	Price
Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'	
Add or subtract price per foot for over or under 11' (includes both reach poles)	\$41.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$3,514.00
4 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$6,479.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$751.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.



### **MODEL 365RF**

### **HEAVY DUTY SUSPENSION WAGON**



- 20 ton HD wagon gear
- Road Flex Suspension
- Quick hitch tongue
- Standard reach length 10'
- Wheel base adjustable 10' 7" 12' 1"
- Hubs 8 Stud 12,000 LBS.
- Disc brake flanges

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
16.5 x 16.1	10 Ply	16.1 x W14C x 8	89"	\$15,732.00	\$12,463.00	\$11,365.00
19L x 16.1	12 Ply	16.1 x W16C x 8	91"	\$16,550.00	\$12,597.00	\$11,365.00
21.5 x 16.1	14 Ply	16.1 x W16C x 8	91"	\$17,977.00	\$12,597.00	\$11,365.00
425 x 22.5	Used Truck*	22.5 x 13 x 8	86"	\$13,756.00	\$12,658.00	\$11,365.00
425 x 22.5	New Truck	22.5 x 13 x 8	86"	\$17,318.00	\$12,658.00	\$11,365.00
445 x 22.5	New Truck	22.5 x 13 x 8	86"	\$17,709.00	\$12,658.00	\$11,365.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 8	86"	\$19,490.00	\$12,658.00	\$11,365.00
560 / 45 x 22.5	16 Ply	22.5 x 16 x 8	92"	\$22,003.00	\$14,378.00	\$11,365.00

Options	Price
Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'	
Add or subtract price per foot for over or under 10' (includes both reach poles)	\$74.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$751.00
Wide Track (Custom Build) up to 90"	\$787.00
Wide Track (Custom Build) over 90"	\$1,245.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$3,514.00
4 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$6,479.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$653.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.



## MODEL 485RF HEAVY DUTY SUSPENSION WAGON



- 24 ton HD wagon gear
- Road Flex Suspension
- Quick hitch tongue
- Standard reach length 10'
- Wheel base adjustable 10' 7" 12' 1"
- Hubs 10 Stud 16,000 LBS.
- Disc brake flanges

Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
425 x 22.5	Used Truck*	22.5 x 13 x 10	86"	\$16,592.00	\$15,494.00	\$14,128.00
425 x 22.5	New Truck	22.5 x 13 x 10	86"	\$20,155.00	\$15,494.00	\$14,128.00
445 x 22.5	New Truck	22.5 x 13 x 10	86"	\$20,545.00	\$15,494.00	\$14,128.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 10	86"	\$22,326.00	\$15,494.00	\$14,128.00
560 / 45 x 22.5	16 Ply	22.5 x 16 x 10	92"	\$24,840.00	\$17,215.00	\$14,128.00

Options	Price
Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'	
Add or subtract price per foot for over or under 10' (includes both reach poles)	\$74.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$751.00
Wide Track (Custom Build) up to 90"	\$787.00
Wide Track (Custom Build) over 90"	\$1,245.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler	\$3,514.00
4 Wheel HD hydraulic disc brakes c/w flat face brake line coupler	\$6,479.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$653.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.



## MODEL 505RF SUSPENSION WAGON

- 22 ton (44,000 lbs.)
- HD tandem wagon gear
- Road Flex Suspension
- Quick hitch tongue
- Standard reach length 10'

- Wheelbase adjustable 10' 7" 12' 1"
- Hubs 8 Stud
- Disc brake flanges
- Safety chain (1/2" Gr. 70)



Tire Size	Tire Type	Rim Size	Track Width	Wagon c/w Tires & Rims	Wagon c/w Rims, Less Tires	Wagon Less Rims, Less Tires
16.5 x 16.1	10 Ply	16.1 x W14C x 8	89"	\$20,515.00	\$15,610.00	\$13,963.00
19L x 16.1	12 Ply	16.1 x W16C x 8	91"	\$21,741.00	\$15,812.00	\$13,963.00
21.5 x 16.1	14 Ply	16.1 x W16C x 8	91"	\$23,882.00	\$15,812.00	\$13,963.00
425 x 22.5	Used Truck*	22.5 x 13 x 8	86"	\$17,550.00	\$15,903.00	\$13,963.00
425 x 22.5	New Truck	22.5 x 13 x 8	86"	\$22,894.00	\$15,903.00	\$13,963.00
445 x 22.5	New Truck	22.5 x 13 x 8	86"	\$23,479.00	\$15,903.00	\$13,963.00
400 / 55 x 22.5	16 Ply	22.5 x 13 x 8	86"	\$26,151.00	\$15,903.00	\$13,963.00
560 / 45 x 22.5	16 Ply	22.5 x 16 x 8	92"	\$29,921.00	\$18,483.00	\$13,963.00

Options	Price
Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'	
Add or subtract price per foot for over or under 10' (includes both reach poles)	\$74.00
Narrow track (Custom Build) down to 60" (stake posts may ship loose)	\$751.00
2 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$3,514.00
4 Wheel HD hydraulic disc brakes c/w flat face brake line coupler, must use 22.5 rim	\$6,479.00
Pioneer male coupler on brake line, in lieu of flat face brake coupler	\$0.00
Single spring balancer	\$122.00
Double spring balancer	\$202.00
4" bolt on riser kit (other heights available)	\$653.00

<sup>\*</sup>Used tires may not meet local regulations, check with your local authority before purchasing.





### CAPACITY OVERVIEW WAGONS AND TRAILERS

		ROAD FLEX		ROAD FLEX	
Features	4-Wheel	4-Wheel	6-Wheel	6-Wheel	
Weight Capacity	6-24 ton	10-24 ton	12-30 ton	18 ton	
Wagon Tongue	Retractable	Retractable	Retractable	Retractable	
Tapered Bearings	Yes	Yes	Yes	Yes	
Ball Joints	Automotive	Automotive	Automotive	Automotive	
Tandem Axle	No	No	Rear	Rear	
Models	145 (8 ton) 185 (10 ton) 185F (6 ton) 205 (12 ton) 275 (14 ton) 285 (15 ton) 365E (20 ton) 485 (24 ton)	185RF (10 ton) 205RF (12 ton) 285RF (15 ton) 365RF (20 ton) 485RF (24 ton)	245 (12 ton) 265 (14 ton) 325 (18 ton) 505 (22 ton) 605 (30 ton)	325RF (18 ton)	

### **WAGON SPECIFICATIONS**

			4 Wheel Models			
Model	145	185	185F	205	275	
Capacity* (30 kph / 20 mph)	16,000 LBS.	20,000 LBS.	12,000 LBS.	24,000 LBS.	28,000 LBS.	
Capacity* (50 kph / 30 mph)	12,000 LBS.	18,000 LBS.	12,000 LBS.	18,000 LBS.	24,000 LBS.	
Spindles	1-3/4" Dia. C1045 Hot Rolled	2" Dia. C1045 Hot Rolled	2" Dia. C1045 Hot Rolled	2-1/4" Dia. C1045 Cold Rolled	2-3/4" Dia. C1045 Cold Rolled	
Hubs	6 Bolt	6 Bolt	6 Bolt	8 Bolt	8 Stud	
Bearings - Bore Size (Inner/Outer)	Taper Roller 1.50 / 1.25	Taper Roller 1.80 / 1.38	Taper Roller 1.80 / 1.38	Taper Roller 1.80 / 1.38	Taper Roller 2.165 / 1.625	
Front Axle	5.5 x 3 x .188 Wall	6 x 3 x .250 Wall	6 x 3 x .250 Wall	7 x 3 x .250 Wall	8 x 3.5x .250 Wall	
Rear Axle	5.5 x 3 x .188 Wall	6 x 3 x .250 Wall	6 x 3 x .250 Wall	7 x 3 x .250 Wall	8 x 3.5 x .250 Wall	
Tongue Bracket Mounting			1-1/2" Bolt Bearing Mtd.			
Tongue Bolt	7/8" Diameter		1-1/8" [	Diameter		
Tongue Latch		Retractable A	utomatic Relock - Standard	on All Models		
Reach Poles		3"	O.D. x .188 Wall - Round Tu	ibe		
Wheel Base			Adjustable			
Bolster Stakes			stable ).5" - 42.5"		42.5" Fixed	
Steering			Automotive Type			
Tie Rod Ends		Grea	sable Automotive Style Ball	Joints		
Height from Ground to Top of Bunk	24" on 11L x 15 Tires	24" on 11L x 15 Tires	24" on 11L x 15 Tires	26" on 12.5 x 16 Tires 30" on 11 x 22.5 Tires	30" on 11 x 22.5 Tires	
Approx. Weight**	535 LBS.	740 LBS.	1,000 LBS.	845 LBS.	1,015 LBS.	
2 Wheel Hyd. Drum Surge Brakes	N/A	N/A	N/A	Optional	Optional	
4 Wheel Hyd. Drum Surge Brakes	N/A	N/A	N/A	N/A	N/A	
2 Wheel Hydraulic Disc Brakes	N/A	N/A	N/A	N/A	Optional	
4 Wheel Hydraulic Disc Brakes	N/A	N/A	N/A	N/A	N/A	
Safety Chain		3/8"	GR. 70		1/2" GR. 70	
Spring Balancer Kit			Optional			
Rocking Bolster	Optional					
4" Bolt on Riser Kit			Optional			

 $<sup>{}^\</sup>star \text{The rated capacities provided are for the chassis only and rims and tires should be matched accordingly when ordered.}$ 



 $<sup>^{\</sup>star\star}$  Noted weights are approximate and less rims and tires.

		ROAD FLEX		ROAD FLEX
Features	8-Wheel (Quad Steer)	8-Wheel (Quad Steer)	Trailer Chassis	Trailer Chassis
Weight Capacity	20-40 ton	20 ton	20-24 ton	20-24 ton
Wagon Tongue	Retractable	Retractable	Clevis Hitch	Clevis Hitch
Tapered Bearings	Yes	Yes	Yes	Yes
Ball Joints	Automotive	Automotive	NA	NA
Tandem Axle	Rear	Rear	Rear	Rear
Models	308 Quad (20 ton) 608 Quad (40 ton)	308RF (20 ton)	TR505 (20 ton) TR605 (24 ton)	TR505RF (20 ton) TR605RF (24 ton)

	6 Wheel Models		8 Wheel	Models
245	265	325	308	608
24,000 LBS.	28,000 LBS.	36,000 LBS.	40,000 LBS.	80,000 LBS.
24,000 LBS.	27,000 LBS.	36,000 LBS.	40,000 LBS.	80,000 LBS.
Front: 2-3/4" Dia. C1045 Cold Rolled Rear: 2-1/4" Dia. C1045 Cold Rolled	2-1/4" Dia. C1045 Cold Rolled	3" Dia. C1045 Cold Rolled	3" Dia. C1045 Cold Rolled	4" Dia. C1045 Cold Rolled
6 Bolt	8 Bolt	8 Stud	8 Stud	10 Stud
Taper Roller 1.80 / 1.38	Taper Roller 1.80 / 1.38	Taper Roller 2.165 / 1.625	Taper Roller 2.165 / 1.625	Taper Roller 2.165 / 1.625
6 x 3 x .250 Wall	7 x 3 x .250 Wall	8 x 3.5 x .250 Wall	8 x 3.5 x .250 Wall	10 x 4 x .500 Wall
6 x 3 x .250 Wall	7 x 3 x .313 Wall	8 x 4 x .250 Wall	8 x 4 x .250 Wall	10 x 4 x .500 Wall
		1-1/2" Bolt Bearing Mtd.		
	1-1/8" D	iameter		1-1/2" Dia.
	Retractable Au	tomatic Relock - Standard	on All Models	
	3" O.D. x .188 Wa	all - Round Tube		6 x 4 x .188 Tubes
		Adjustable		
Adjustable 38.5" - 40.5" - 42.5"		42.5"	Fixed	
		Automotive Type		
	Gr	easable Automotive Style Ball Join	ts	
23" on 11L x 15 Tires	26" on 12.5 x 16 Tires	30" on 11 x 22.5 Tires	30" on 11 x 22.5 Tires	24" on 445/65 x 22.5 Tires
985 LBS.	1,155 LBS.	1,495 LBS.	2,135 LBS.	3,020 LBS.
N/A	Optional	N/A	N/A	N/A
N/A	Optional	N/A	N/A	N/A
N/A	N/A	Optional	Optional	Optional
N/A	N/A	Optional	Optional	Optional
3/8" GR. 70		1/2" GR 70		5/8" GR 70
		Optional		
	Optional		N/A	Standard

<sup>\*</sup>The rated capacities provided are for the chassis only, tire size determines GVWR





<sup>\*\*</sup> Noted weights are approximate and less rims and tires.



### **HEAVY DUTY WAGON SPECIFICATIONS**

	4 Wheel Models			
Model	285	365E	365	485
Capacity* (30 kph / 20 mph)	30,000 LBS.	40,000 LBS.	40,000 LBS.	48,000 LBS.
Capacity* (50 kph / 30 mph)	24,000 LBS.	36,000 LBS.	36,000 LBS.	48,000 LBS.
Spindles	2-3/4" Dia. C1045 Cold Rolled	3" Dia. 1144 Stress Proof	3" Dia. 1144 Stress Proof	4" Dia. C1045 Cold Rolled
Hubs	8 Stud	8 Stud	8 Stud	10 Stud
Front Axle	8 x 4 x .250 Wall	10 x 4 x .250 Wall	10 x 4 x .250 Wall	10 x 4 x .500 Wall
Rear Axle	8 x 4 x .188 Wall	10 x 4 x .188 Wall	10 x 4 x .188 Wall	10 x 4 x .375 Wall
Tongue Bracket Mounting		1-1/2" Bolt E	Bearing Mtd.	
Tongue Bolt	1-1/8" Dia.	1-1/8" Dia.	1-1/8" Dia.	1-1/2" Dia.
Bolster		Flexible	e Front	
Reach Tubes		6 x 4 x .1	88 Tubes	
Bolster Stakes		42.5"	Fixed	
Steering		Automot	ive Type	
Tie Rod Ends		Greasable Automot	ive Style Ball Joints	
Wheel Base		Adjus	stable	
Height from Ground to Top of Bunk	32" on 445/65 x 22.5 Tires	34" on 445/65 x 22.5 Tires	34" on 445/65 x 22.5 Tires	34" on 445/65 x 22.5 Tires
Approx. Weight**	1,445 LBS.	1,495 LBS.	1,595 LBS.	2,210 LBS.
2 Wheel Hydraulic Disc Brakes		Opti	onal	
4 Wheel Hydraulic Disc Brakes	N/A N/A N/A			
Safety Chain	1/2" GR 70 5/8" GR 70			
Spring Balancer Kit	Optional			
Rocking Bolster	Standard			
4" Bolt on Riser Kit		Opti	onal	

	6 Wheel	Models		
Model	505	605		
Capacity* (30 kph / 20 mph)	44,000 LBS.	60,000 LBS.		
Capacity* (50 kph / 30 mph)	44,000 LBS.	60,000 LBS.		
Spindles	3" Dia. 1144 Stress Proof	4" Dia. C1045 Cold Rolled		
Hubs	8 Stud	10 Stud		
Front Axle	10 x 4 x .250 Wall	10 x 4 x .500 Wall		
Rear Axle	10 x 4 x .375 Wall	10 x 4 x .500 Wall		
Tongue Bracket Mounting	1-1/2" Bolt E	Bearing Mtd.		
Tongue Bolt	1-1/8" Dia.	1-1/2" Dia.		
Bolster	Flexible Front			
Reach Tubes	6 x 4 x .188 Tubes			
Bolster Stakes	42.5" Fixed			
Steering	Automotive Type			
Tie Rod Ends	Greasable Automotive Style Ball Joints			
Wheel Base	Adjustable			
Height from Ground to Top of Bunk	32" on 445/65 x 22.5 Tires	34" on 445/65 x 22.5 Tires		
Approx. Weight**	2,405 LBS.	3,295 LBS.		
2 Wheel Hydraulic Disc Brakes	Opti	onal		
4 Wheel Hydraulic Disc Brakes	Optional			
Safety Chain	1/2" GR 70 5/8" GR 70			
Spring Balancer Kit	Optional			
Rocking Bolster	Standard			
4" Bolt on Riser Kit	Optional			



<sup>\*</sup>The rated capacities provided are for the chassis only, tire size determines GVWR

<sup>\*\*</sup> Noted weights are approximate and less rims and tires.

## HORST ROAD FLEX SUSPENSION WAGON SPECIFICATIONS

Model         185RF         205RF         285RF         365RF         485RF           Capacity* (30 kph / 20 mph)         20,000 LBS.         24,000 LBS.         30,000 LBS.         40,000 LBS.         48,000 LBS.           Capacity* (50 kph / 30 mph)         18,000 LBS.         18,000 LBS.         24,000 LBS.         36,000 LBS.         48,000 LBS.           Spindles         2° Dia C1045 Hot Rolled         2-1/4" Dia C1045 Cold Rolled         2° TS" Dia C1045 Stress Proof         Cold Rolled           Hubs         6 Bolt         8 Bolt         8 Stud         8 Stud         10 Stud           Front Avde         6 x3 x 250 Wall         7 x3 x 250 Wall         8 x4x x 250 Wall         10 x4x 250 Wall         10 x4x 250 Wall         10 x4x x 375 Wall           Rear Avde         6 x3 x 250 Wall         7 x3 x 250 Wall         8 x4x x 188 Wall         10 x4x x 188 Wall         10 x4x x 375 Wall         10 x4x x 188 Wall         10				4 Wheel Models		
Capacity* (50 kph / 30 mph)         18,000 LBS.         18,000 LBS.         24,000 LBS.         36,000 LBS.         48,000 LBS.           Spindles         2° Dia C1045 Hot Rolled         2-1/4° Dia C1045 Cold Rolled         2.75° Dia C1045 Stress Proof         3° Dia 1144 A° Dia C1045 Cold Rolled           Hubs         6 Bolt         8 Bolt         8 Stud         8 Stud         10 Stud           Front Axle         6 x3 x250 Wall         7 x3 x250 Wall         8 x4 x250 Wall         10 x4 x2	Model	185RF	205RF	285RF	365RF	485RF
Spindles         2" Dia. C1045 Hot Rolled         2-1/4" Dia. C1045 Cold Rolled         2.75" Dia. C1045 Cold Rolled         3" Dia. 1144 Stress Proof         4" Dia. C1045 Cold Rolled           Hubs         6 Bolt         8 Bolt         8 Stud         8 Stud         10 Stud           Front Axle         6 x3 x 250 Wall         7 x 3 x 250 Wall         8 x 4 x 250 Wall         10 x 4 x 250 Wall         10 x 4 x 250 Wall         10 x 4 x 30 Wall           Rear Axle         6 x 3 x 250 Wall         7 x 3 x 250 Wall         8 x 4 x .188 Wall         10 x 4 x .188 Wall         10 x 4 x .35 Wall           Tongue Bracket Mounting         1-1/8" Dia.         4-1/8" Dia.         4-1/8" Dia.         4-1/8" Dia.         4-1/8" Dia.         4-1/8" Dia.         4-1/8" D	Capacity* (30 kph / 20 mph)	20,000 LBS.	24, 000 LBS.	30,000 LBS.	40,000 LBS.	48,000 LBS.
Hot Rolled         Cold Rolled         Cold Rolled         Stress Proof         Cold Rolled           Hubs         6 Bolt         8 Bolt         8 Stud         8 Stud         10 Stud           Front Axle         6 x3 x 250 Wall         7 x 3 x 250 Wall         8 x 4 x 250 Wall         10 x 4 x 250 Wall         10 x 4 x 250 Wall         10 x 4 x 370 Wall           Rear Axle         6 x3 x 250 Wall         7 x 3 x 250 Wall         8 x 4 x 188 Wall         10 x 4 x 188 Wall <td>Capacity* (50 kph / 30 mph)</td> <td>18,000 LBS.</td> <td>18,000 LBS.</td> <td>24,000 LBS.</td> <td>36,000 LBS.</td> <td>48,000 LBS.</td>	Capacity* (50 kph / 30 mph)	18,000 LBS.	18,000 LBS.	24,000 LBS.	36,000 LBS.	48,000 LBS.
Front Axle         6x3x 250 Wall         7x3x 250 Wall         8x4x 250 Wall         10x4x 250 Wall         10x4x 250 Wall           Rear Axle         6x3x 250 Wall         7x3x 250 Wall         8x4x 188 Wall         10x4x 188 Wall         10x4x 375 Wall           Tongue Bott         1-1/8" Dia.         1-1/8" Dia.         1-1/8" Dia.         1-1/8" Dia.         1-1/8" Dia.         1-1/8" Dia.         1-1/2" Dia.           Bolster         N/A         Illevible Front         Flexible Front         Flexi	Spindles					
Rear Axide         6 x3 x 250 Wall         7 x3 x 250 Wall         8 x 4 x 188 Wall         10 x 4 x .188 Wall         10 x 4 x .188 Wall         10 x 4 x .375 Wall           Tongue Bracket Mounting         1-1/8" Dia.         1-1/8" Dia.         1-1/8" Dia.         1-1/8" Dia.         1-1/8" Dia.         1-1/8" Dia.         1-1/2" Dia.           Bolster         N/A         Flexible Front         Flexible Front <td>Hubs</td> <td>6 Bolt</td> <td>8 Bolt</td> <td>8 Stud</td> <td>8 Stud</td> <td>10 Stud</td>	Hubs	6 Bolt	8 Bolt	8 Stud	8 Stud	10 Stud
Tongue Bracket Mounting         1-1/2" Bolt Bearing Mtd.           Tongue Bolt         1-1/8" Dia.         1-1/2" Dia.           Bolster         N/A         I Bexible Front         Flexible Front         6 x 4 x .188 Tubes         1-1/2" Bolt Bearing Mtd.         1-1/2" Dia.         1	Front Axle	6 x 3 x .250 Wall	7 x 3 x .250 Wall	8 x 4 x .250 Wall	10 x 4 x .250 Wall	10 x 4 x .500 Wall
Tongue Bolt         1-1/8" Dia.	Rear Axle	6 x 3 x .250 Wall	7 x 3 x .250 Wall	8 x 4 x .188 Wall	10 x 4 x .188 Wall	10 x 4 x .375 Wall
Bolster         N/A         Flexible Front           Reach Tubes         3" 0.D. x.188 Wall Round Tube         6 x 4 x.188 Tubes           Bolster Stakes         Adj. 38.5" - 40.5" - 42.5"         42.5" Fixed           Steering         Automotive Type           Tie Rod Ends         Greasable Automotive Style Ball Joints           Wheel Base         Adjustable           Height from Ground to Top of Bunk         26" on 11Lx15 Tires         27" on 12.5 x 16 Tires 31" on 11 x 22.5 Tires         39" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         40" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         350 LBs         4,370 LBs         4,370 LBs         4,370 LBs         22" on 11/2" GR 70         5/8" GR 70	Tongue Bracket Mounting			1-1/2" Bolt Bearing Mtd.		
Reach Tubes         3" 0.D. x.188 Wall Round Tube         6 x 4 x.188 Tubes           Bolster Stakes         Adj. 38.5" - 40.5" - 42.5"         42.5" Fixed           Steering         Automotive Type           Tie Rod Ends         Greasable Automotive Style Ball Joints           Wheel Base         Adjustable           Height from Ground to Top of Bunk         26" on 11Lx15 Tires         27" on 12.5 x16 Tires 31" on 11x 22.5 Tires         39" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         40" on 445/65 x 22.5 Tires           Approx. Weight**         1,150 LBS.         1,270 LBS.         3,085 LBS.         3,505 LBS.         4,370 LBS.           2 Wheel Hydraulic Disc Brakes         N/A         N/A         Optional           4 Wheel Hydraulic Disc Brakes         N/A         N/A         Optional           Safety Chain         3/8" GR 70         5/8" GR 70           Spring Balancer Kit         Optional         5/8" GR 70	Tongue Bolt	1-1/8" Dia.	1-1/8" Dia.	1-1/8" Dia.	1-1/8" Dia.	1-1/2" Dia.
Bolster Stakes         Adj. 38.5" - 40.5" - 42.5"         42.5" Fixed           Steering         Automotive Type           Tie Rod Ends         Greasable Automotive Style Ball Joints           Wheel Base         Adjustable           Height from Ground to Top of Bunk         26" on 11Lx15 Tires         27" on 12.5x 16 Tires 31" on 11 x 22.5 Tires         39" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         40" on 445/65 x 22.5 Tires         30" on 445/65 x 22.5 Tires         30	Bolster	N/A			Flexible Front	
Steering         Automotive Type           Tie Rod Ends         Greasable Automotive Style Ball Joints           Wheel Base         Adjustable           Height from Ground to Top of Bunk         26" on 11Lx15 Tires         27" on 12.5 x 16 Tires 31" on 11 x 22.5 Tires 31" on 145/65 x 22.5 Tires 31" on 445/65 x 22.5 Tires 3	Reach Tubes	3" O.D. x .188 Wall Round Tube		6 x 4 x .188 Tubes		
Tie Rod Ends         Greasable Automotive Style Ball Joints           Wheel Base         Adjustable           Height from Ground to Top of Bunk         26" on 11Lx15 Tires         27" on 125 x 16 Tires 31" on 11 x 22.5 Tires         39" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         40" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         NO         50" on 45/65 x 22.5	Bolster Stakes	Adj. 38.5" -	40.5" - 42.5"	42.5" Fixed		
Wheel Base         Adjustable           Height from Ground to Top of Bunk         26" on 11Lx15 Tires         27" on 125 x 16 Tires 31" on 11 x 22.5 Tires         39" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         40" on 445/65 x 22.5 Tires         3,085 LBS.         3,505 LBS.         4,370 LBS.         4,370 LBS.         2 Wheel Hydraulic Disc Brakes         N/A         N/A         Optional         5/8" GR 70	Steering			Automotive Type		
Height from Ground to Top of Bunk         26" on 11Lx15 Tires         27" on 12.5 x 16 Tires 31" on 11 x 22.5 Tires         39" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         39" on 445/65 x 22.5 Tires         40" on 445/65 x 22.5 Tires         30" on 445/65 x 22.5 Tires         40" on 445/65 x 22.5 Tires         40" on 445/65 x 22.5 Tires         40" on 445/65 x 22.5 Ti	Tie Rod Ends		Gre	asable Automotive Style Ball Joints	;	
Approx. Weight** 1,150 LBS. 1,270 LBS. 3,085 LBS. 3,505 LBS. 4,370 LBS. 2 Wheel Hydraulic Disc Brakes N/A N/A Optional  4 Wheel Hydraulic Disc Brakes N/A N/A Optional  Safety Chain 3/8" GR 70 1/2" GR 70 5/8" GR 70  Spring Balancer Kit Optional	Wheel Base			Adjustable		
2 Wheel Hydraulic Disc Brakes N/A N/A Optional 4 Wheel Hydraulic Disc Brakes N/A N/A Optional  Safety Chain 3/8" GR 70 1/2" GR 70 5/8" GR 70  Spring Balancer Kit Optional	Height from Ground to Top of Bunk	26" on 11Lx15 Tires		39" on 445/65 x 22.5 Tires	39" on 445/65 x 22.5 Tires	40" on 445/65 x 22.5 Tires
4 Wheel Hydraulic Disc Brakes N/A N/A Optional Safety Chain 3/8" GR 70 1/2" GR 70 5/8" GR 70 Spring Balancer Kit Optional	Approx. Weight**	1,150 LBS.	1,270 LBS.	3,085 LBS.	3,505 LBS.	4,370 LBS.
Safety Chain         3/8" GR 70         1/2" GR 70         5/8" GR 70           Spring Balancer Kit         Optional	2 Wheel Hydraulic Disc Brakes	N/A	N/A		Optional	
Spring Balancer Kit Optional	4 Wheel Hydraulic Disc Brakes	N/A	N/A		Optional	
	Safety Chain	3/8" GR 70		1/2" GR 70		5/8" GR 70
Rocking Bolster N/A N/A N/A N/A N/A N/A	Spring Balancer Kit			Optional		
	Rocking Bolster	N/A	N/A	N/A	N/A	N/A
4" Bolt on Riser Kit Optional	4" Bolt on Riser Kit			Optio	onal	

6 Wheel	Models	8 Wheel Models
325RF	505RF	308RF
36,000 LBS.	44,000 LBS.	40, 000 LBS.
36,000 LBS.	44,000 LBS.	40, 000 LBS.
3" Dia. C1045 Cold Rolled	3" Dia. 1144 Stress Proof	3" Dia. C1045 Cold Rolled
8 Stud	8 Stud	8 Stud
8 x 3.5 x .250 Wall	10 x 4 x .250 Wall	8 x 3.5 x .250 Wall
8 x 4 x .250 Wall	10 x 4 x .375 Wall	8 x 4 x .250 Wall
	1-1/2" Bolt Bearing Mtd.	
1-1/8" Dia.	1-1/2" Dia.	1-1/8" Dia.
N/A	N/A	N/A
3" O.D. x .188 Wall Round Tube	6 x 4 x .188 Tubes	3" O.D. x .188 Wall Round Tube
	42.5" Fixed	
	Automotive Type	
(	Greasable Automotive Style Ball Joint	S
	Adjustable	
33" on 11 x 22.5 Tires	32" on 445/65 x 22.5 Tires	33" on 11 x 22.5 Tires
2,185 LBS.	3,325 LBS.	3,030 LBS.
	Optional	
	Optional	
	1/2" GR 70	
	Optional	
	N/A	
	Optional	
	325RF 36,000 LBS. 36,000 LBS. 37 Dia. C1045 Cold Rolled 8 Stud 8 x35 x 250 Wall 8 x 4 x .250 Wall 1-1/8" Dia. N/A 3" O.D. x .188 Wall Round Tube	36,000 LBS. 44,000 LBS. 36,000 LBS. 44,000 LBS. 3 " Dia. C1045 3" Dia. 1144 Cold Rolled Stress Proof  8 Stud 8 Stud 8 Stud  8 x3.5 x 250 Wall 10 x4 x 250 Wall  8 x4 x .250 Wall 10 x4 x .375 Wall  1-1/2" Bolt Bearing Mtd.  1-1/2" Dia. 1-1/2" Dia.  N/A N/A  3" O.D. x .188 Wall Round Tube 6 x 4 x .188 Tubes  42.5" Fixed  Automotive Type  Greasable Automotive Style Ball Joint  Adjustable  33" on 11 x 22.5 Tires 32" on 445/65 x 22.5 Tires  2,185 LBS. 0ptional  Optional  1/2" GR 70  Optional  N/A


<sup>\*</sup>The rated capacities provided are for the chassis only, tire size determines GVWR



<sup>\*\*</sup> Noted weights are approximate and less rims and tires.

### TRAILER CHASSIS SPECIFICATIONS

	Trailer	Chassis			
Model	TR505	TR605	TR505RF	TR605RF	
Capacity* (30 kph / 20 mph)	40,000 LBS.	48,000 LBS.	40,000 LBS.	48,000 LBS.	
Capacity* (50 kph / 30 mph)	36,000 LBS.	48,000 LBS.	36,000 LBS.	48,000 LBS.	
Spindles	3" Dia. 1144 Stress Proof	4" Dia. C1045 Cold Rolled	3" Dia. 1144 Stress Proof	4" Dia. C1045 Cold Rolled	
Hubs	8 Stud	10 Stud	8 Stud	10 Stud	
Bolster Stakes	42.5"	Fixed	42.5" Fixed		
Height from Ground to Top of Bunk	32" on 445/65 x 22.5 Tires	34" on 445/65 x 22.5 Tires	39" on 445/65 x 22.5 Tires	40" on 445/65 x 22.5 Tires	
Approx. Weight**	2,700 LBS.	3,775 LBS.	<b>5,270</b> LBS.	<b>5,885</b> LBS.	
2 Wheel Hydraulic Disc Brakes	Opti	Optional		Optional	
4 Wheel Hydraulic Disc Brakes	Optional		Opti	onal	
Safety Chain	1/2" GR 70	5/8" GR 70	1/2" GR 70	5/8" GR 70	
4" Bolt on Riser Kit	Opti	onal	Opti	onal	



Bolster Measurement A	137"	137"	140"	140"
Bolster Measurement B	156"	182"	156"	182"
Bolster Measurement C	128"	134"	101"	107"
Bolster Measurement D	28"	48"	55"	75"

<sup>\*</sup>The rated capacities provided are for the chassis only, tire size determines GVWR



 $<sup>\</sup>ensuremath{^{**}}$  Noted weights are approximate and less rims and tires.

### **STANDARD & OPTIONAL EQUIPMENT FOR RUNNING GEAR**

NOTE: Standard and optional running gear equipment varies. Verify features and options availability on model page.

### **Rocking Bolster**









Our heavy duty bolsters let you solidly attach your load from Gravity Bins to Hay Racks. The Rocking Bolster design allows heavy loads some flex and movement reducing stress on the running gear and providing a better ride. Rocking bolsters are standard equipment on all square tube equipped non-suspension running gear.

4" bolt on riser kit for extra bunk height clearance. *Note: other heights available.* 

Riser Kits

### **Brake Systems**





For added safety and stopping power we have brake systems available in drum and disc configurations.

### **Spring Balancers**





For tongue consisting of spring adjustable bolt and two bolt-on brackets.

### **Safety Chains**



Our Grade 70 safety chains in 3/8 and 1/2 inch sizes make sure your wagon is secure.



### **NEW IMPLEMENT TIRES (FARM UTILITY)**

Tire	Ply	Capacity (Lbs/tire)	Description
26 x 12	12 Ply	2,750	Tubeless Tires on 12 x 10.5 x 6 rims
11L x 15	8 Ply	2,540	Farm Utility Tubeless
12.5L x 15	12 Ply	3,640	Farm Utility Tubeless
12.5L x 16	14 Ply	4,180	Farm Utility Tubeless
14L x 16.1	8 Ply	3,860	Farm Utility Tubeless
14L x 16.1	12 Ply	4,680	Farm Utility Tubeless
16.5 x 16.1	10 Ply	5,200	Farm Utility Tubeless
19L x 16.1	10 Ply	6,000	Farm Utility Tubeless
21.5 x 16.1	14 Ply	7,850	Farm Utility Tubeless

Tire Ratings are at 25 mph.



26x12 12 Ply



11L x 15 8 Ply



12.5L x 15 12 Ply



12.5L x 16 14 Ply



14L x 16.1 8 Ply



14L x 16.1 12 Ply



16.5 x 16.1 10 Ply



19L x 16.1 10 Ply



21.5 x 16.1 14 Ply

<sup>\*\*</sup> Images shown for approximate size and profile of tire and rim package only. Relative wheel picture sizing is approximate.



### **NEW IMPLEMENT TIRES (HIGHWAY SERVICE)**

Tire	Load Range	Capacity (Lbs/tire)	Description
20.5 x 8-10	F	1,800	Tires on 10 x 6 x 6 rims
225/75 R15	D	2,540	Highway Trailer Tubeless Tires on 15 x 6 x 6 rims
235/85 R16	F	3,960	Highway Trailer Tubeless Tires on 16 x 8 x 6 rims
400/55 x 22.5	16 Ply	7,820	Highway Flotation Tubeless Tires on 22.5 x 13
550/45 x 22.5	16 Ply	9,640	Highway Flotation Tubeless Tires on 22.5 x 16
11L x 15	D	3,120	Highway Service Tubeless Tires Must be used with HD rims
11L x 15	F	3,960	Highway Service Tubeless Tires Must be used with HD rims
11L x 15	F	3,690	Highway Service Tubeless Tires for Header Wagon
12.5L x 15	F	4,680	Highway Service Tubeless Tires Must be used with HD rims

Tire Ratings are at 25 mph.



20.5 x 8-10 Load Range F



225/75 R15 Load Range D



235/85 R16 Load Range F



11L x 15 Load Range F



11L x 15 Load Range D



11L x 15 Load Range F



12.5L x 15 Load Range F

Available Sizes: 550/45 x 22.5 16 Ply 400/55 x 22.5 16 Ply



<sup>\*\*</sup> Images shown for approximate size and profile of tire and rim package only. Relative wheel picture sizing is approximate.



### **USED TRUCK TIRES**

Tire	Tubeless	Capacity (Lbs/tire)*	Rim Size Required
245 R16	New Tubes	3,500	16×8
11 x 22.5	Tubeless	8,000	22.5 x 8.25 HD
12 or 315 x 22.5	Tubeless	8,000	22.5 x 8.25 HD
305 x 22.5	Tubeless	8,000	22.5 x 8.25 HD
385 x 22.5 (15 x 22.5)	Tubeless	10,000	22.5 x 11.25 / 22.5 x 11.75
425 x 22.5 (16 x 22.5)	Tubeless	12,000	22.5 x 13 / 22.5 x 11.25 / 22.5 x 11.75

<sup>\*</sup> Capacities on used tires are approximate





385 x 22.5 (15 x 22.5)

425 x 22.5 (16 x 22.5)

## USED TIRE WARRANTY

We do our own mounting and use only new tubes. They will all be marked and dated. Any tire which goes flat within 90 days of purchase, we will exchange free if it is returned on the rim that it went flat on.

We do not accept repair bills sent to us.

<sup>\*\*</sup> Images shown for approximate size and profile of tire and rim package only. Relative wheel picture sizing is approximate.



### **RECAP TRUCK TIRES**

Tire	Tubeless	Capacity (Lbs/tire)*	Rim Size Required
11 x 22.5	Tubeless	8,000	22.5 x 8.25 HD
12 or 315 x 22.5	Tubeless	8,000	22.5 x 8.25 HD
305 x 22.5	Tubeless	8,000	22.5 x 8.25 HD
385 x 22.5 (15 x 22.5)	Tubeless	10,000	22.5 x 11.25 / 22.5 x 11.75
425 x 22.5 (16 x 22.5)	Tubeless	12,000	22.5 x 13 / 22.5 x 11.25 / 22.5 x 11.75
445 / 50 x 22.5	Tubeless	12,000	22.5 x 13

<sup>\*</sup> Capacities on recap tires are approximate







305 x 22.5



12 or 315 x 22.5



385 x 22.5 (15 x 22.5)



425 x 22.5 (16 x 22.5)



445 / 50 x 22.5

<sup>\*\*</sup> Images shown for approximate size and profile of tire and rim package only. Relative wheel picture sizing is approximate.



### **Reach Pole Guidelines**

Guidelines for Reach Pole Length Requirements						
	4 Wheel Std.	6 Wheel Std.	8 Wheel Std.	4 Wheel HD	6 Wheel HD	8 Wheel HD
Forage Box Length						
16'	11' Round	11' Round	9' Round	10' Square	10' Square	N/A
18'	12' Round	12' Round	9' Round	12' Square	12' Square	8' Square
20'	14' Round	14' Round	11' Round	14' Square	14' Square	10' Square
Flat Rack and/or Bale Carrier Length						
16'	WA145 - 6'7" Round Other Models - 11' Round	11' Round	9' Round	10' Square	N/A	N/A
18'	12' Round	12' Round	9' Round	10' Square	N/A	N/A
20'	14' Round	14' Round	11' Round	12' Square	N/A	N/A
25'	18' Round	16' Round	14' Round	16' Square	N/A	N/A
30'	22' Round	20' Round	18' Round	20' Square	18' Square	16' Square
36'	N/A	24' Round (Requires Support)	20' Round	24' Square	22' Square	18' Square
Gravity Box Sizes						
250 Bu.	12 to 14 Ton Wagon 9' Round	N/A	N/A	N/A	N/A	N/A
250-500 Bu.	12 to 14 Ton Wagon 11' Round	N/A	N/A	8' Square	N/A	N/A
500-600 Bu.	N/A	N/A	N/A	10' Square	N/A	N/A
750 Bu.	N/A	N/A	N/A	14' Square	N/A	N/A

