

CEMENT MIXERS



Hydraulic/PTO Concrete Mixers



Worksaver's Skid Steer Mixer, model SS-590 has direct hydraulic drive of the gearbox which eliminates chain and sprocket maintenance resulting in more up-time on the jobsite. Large 11-cubic ft. drum allows the operator to mix, transport and place 5-cubic ft. of concrete. It's efficient design offers the contractor a cost savings over chain driven models.

- All welded steel drum construction with internal paddles for uniform mixing and clean dumping.
- Compact, trouble free, long life design with few moving parts.
- Direct hydraulic drive of the gearbox eliminates chain & sprocket maintenance.
- Flow control valve allows easy control of mixer speed.
- All welded frame "universal" skid steer with step-through design for easy access to the operators' seat.

Model 580 3-pt. mixer is ideal for mixing feed, fertilizer, inoculating seed, potting soil and other mixing jobs.

Hydraulic top link cylinder provides positive dump control. Number 40-roller chain drives mixing drum. Adjustable Cat.I hitch allows easy hook up to most tractors (7/8" dia. lift pins). Sealed ball bearings provide long service life with reduced maintenance.



Concrete Mixer Specifications

	580	SS-590
Capacity	Five (5) cu/ft (1 Bag Mix)	Five (5) cu/ft (1 Bag Mix)
Drum Opening (in/cm)	17.5 / 44	20 / 51
Overall Drum Length (in/cm)	32 / 81	32 / 81
Drum Construction	2-Piece Bolted	Welded Steel
Drive System	Tractor PTO	Hydraulic Direct Thru Gearbox
Hydraulic Requirements	N/A	Minimum 8 GPM
Hitch Requirements	Cat. I (7/8" dia. lift pins)	N/A
Drive Ratio	8.77:1	3.18:1
Flow Control Valve	N/A	Standard
Connect Under Pressure Couplers	N/A	Standard
Parking Stands	Standard	Standard
Shipping Weight (lbs/kg)	253 / 115	395 / 180
Product No.	780620	780950




WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

CEMENT MIXERS

Prices Effective as of 4-22



Land Management Attachments

Designed for use on Skid Steer Loaders					
	SS-590	780950	Skid Steer Mixer. 5 Cu. Ft. (1 bag mix). Hydraulic driven mixer with parking stands. Internally welded mixing paddles for proper mixing. Includes flow control valve (on/off) for easy operation. Hoses includes flat-faced couplers.	395	5,530.00
Optional Flat-Face Coupler Set					
		2505650	Flat-Faced Coupler Set interfaces w/ standard ends on our SS attachments. 1 ea. 1/2" male 1 ea. 1/2" female coupler	3	259.00



Prices and Specifications may be subject to change without notice. Prices do not include shipping or setup.