



RTG2 ROTARY TEDDER



Features

- 5.600-6 Wheels
- 12 Flexible steel teeth
- Cardan shaft with slip clutch
- Oil bath gear box
- Working Width = 10' 2"
- Transport Width = 8' 2"
- Weight = 419 lbs.

RTG2 Rotary Tedder

- BASE UNIT**
- ❖ 2 Rotors
 - ❖ 5.600-6 Wheels
 - ❖ 12 Flexible Steel Teeth
 - ❖ 540 PTO Shaft w/Slip Clutch
 - ❖ Oil Bath Gearbox
 - ❖ 10' 2" Working Width

Item #	Description	List Price
RTG2	Pull-Type Rotary Tedder	\$4,152





RT-5200 & 5800 ROTARY TEDDERS



Specifications

RT-5200H

NUMBER OF ROTARS	4
TINE ARMS ON ROTARS	6
WORKING WIDTH	17'
TRANSPORT WIDTH	10' 3"
WEIGHT	1000#
TIRES	16x6 5-8
TRACTOR HP REQUIRED	25
PTO SLIP CLUTCH	Standard
OPERATING SPEED	10 MPH

RT-5800H

NUMBER OF ROTARS	4
TINE ARMS ON ROTARS	6
WORKING WIDTH	19'
TRANSPORT WIDTH	11'
WEIGHT	1225#
TIRES	16x6 5-8
TRACTOR HP REQUIRED	25
PTO SLIP CLUTCH	Standard
OPERATING SPEED	10 MPH



RT-5200-H & RT-5800-H Rotary Tedder

- BASE UNIT**
- ❖ 4 Rotors
 - ❖ Hydraulic Fold Wings/Rotors
 - ❖ 16 x 6.50-8 Wheels
 - ❖ Flexible Steel Teeth
 - ❖ 540 PTO Shaft w/Slip Clutch
 - ❖ Oil Bath Gearbox

Item #	Description	List Price
RT-5200-H	Pull-Type Rotary Tedder 17' Working Width	\$10,027
RT-5800-H	Pull-Type Rotary Tedder 19' Working Width	\$11,693
OPTIONS (<u>NOT</u> Required)		
TROHYDT	Hydraulic Tilt for RT-5200-H & RT-5800-H (Dealer Installed)	\$1,010





RTG6 ROTARY TEDDER



Features

- Central tandem wheels to adapt to any type of terrain
- Grease lubricated unit
- 540 rpm
- Heavy Duty shielded PTO shaft with clutch protection
- 16.650-8 Wheels
- 36 Flexible steel teeth
- Working Width = 24'
- Transport Width = 9' 8"
- Weight = 1917 lbs.

RTG6 Rotary Tedder

- BASE UNIT**
- ❖ 16 x 6.50-8 Wheels
 - ❖ 36 Flexible Steel Teeth
 - ❖ 540 Heavy-Duty PTO Shaft w/Clutch Protection
 - ❖ Oil Bath Gearbox
 - ❖ 24' Working Width

Item #	Description	List Price
RTG6	Pull-Type Rotary Tedder	\$19,570

