

H&S

TF6128 TWIN-FLEX MERGERS

The ability (with up to 16' windrow cuts) to merge (5) Windrows into one in either direction.....*No additional Cross-Conveyor Extension is needed!*



❖ **Patented Center Cam/Center Drive Design Provides Smooth Clump Free Windrows - NO BUNCHING!**

❖ **The Twin-Flex has the WIDEST Cross-Conveyor Belt in its' class at 42".**

- ❖ **28' of Continuous Merging with (2) 14' independent Heads.**
- ❖ **The Self-Contained Hydraulic System features a 35 gallon reservoir coupled with large displacement motors for the Heads and Cross Conveyor, is able to handle "HEAVY" Crops.**
- ❖ **Patented Center Cam/Center Drive System.**
- ❖ **Rubber Mounted Teeth.**
- ❖ **Highest Torque Rated Hydraulic Motors in the Industry, coupled with Heavy 2-Ply Cross-Conveyor Belts.**
- ❖ **Cross-Conveyor Belts feature a High Torque Drive System....Best in the Industry!**
- ❖ **Both Models have the ability to merge Left, merge Right, or Split Direction.**
- ❖ **Requires no Sensors to run the Machine. Very simple to operate.**

TF6128 TWIN-FLEX MERGER FEATURES



❖ **Best-Value per Linear Foot of Machine Width for a (2) Head Continuous Merger**

The H&S **SOFT SHOE™** Suspension System (patent pending) is a self-contained, self-monitoring hydraulic suspension system for the TF6128 TWIN FLEX™ Merger that provides the softest merger head footprint in the industry, and in all field conditions...wet soils, rough terrain, new seeding, etc.



TF6128

Working Width	28'2"
Transport Width	8' 6"
Transport Length	25'
Transport Height	9'8"
Pick-up Heads	2 – 14'
Head Travel	20"
Pick-up Strippers	Poly
Pick-up Teeth	Rubber Mounted
Conveyor Belt Width	42"
Cross-Conveyor On/Off Right/Left/Split	In-Cab Electric-over-Hydraulic
Skid Shoe Height	Manual Adjust
Head Suspension	Exclusive "Soft Shoe" Suspension Technology System with In-Cab-Adjust
Drive System	3-Section High Volume Pump
PTO	1000 RPM 1-3/8" or 1-3/4"
Oil Reservoir Capacity	35 Gallon
Tire Size	15R x 19.5
Weight	12,260#
Tractor Size	95 HP Minimum
Hydraulic Requirements	2 Sets of Remotes (Requires Closed Center Hydraulic System) 2750 PSI 12 GPM min.
3-Point Hitch	Cat II, III, or III-N



TF6128 TWIN-FLEX MERGER

BASE UNIT	<ul style="list-style-type: none"> ❖ Exclusive “SOFT-SHOE” Suspension Technology ❖ 28’ 2” Continuous Working Width w/Two Heads ❖ Self Contained Hydraulic System ❖ 3-Section High Volume Pump ❖ 35 Gallon Oil Reservoir ❖ 2 Sets of Remotes Needed ❖ Patented Center Cam/Center Drive ❖ Rubber Mounted Teeth ❖ 42” Wide Cross-Conveyor ❖ Manual Hydraulic Controls ❖ Electric In-Cab Controls for Cross-Conveyor Right/Left/Split/Shut-off ❖ Manual Adjust Skid Shoes ❖ 15R19.5 Radial Tires w/Rims ❖ Cat II, III, or III-N 3-Point Hitch ❖ Weight - 12,260# 	
Item #	Description	List Price
TF6128	Twin-Flex Merger w/Exclusive “SOFT-SHOE” Suspension Package & Electric Cab Controls	\$146.839

PTO CHOICES (Required)		
TFO1038PTO	1-3/8” 1000 RPM Standard Length PTO	\$1,084
TFO1038LPTO	1-3/8” 1000 RPM Long Length PTO	\$1,084
TFO1034PTO	1-3/4” 1000 RPM Standard Length PTO	\$1,158
TFO1034LPTO	1-3/4” 1000 RPM Long Length PTO	\$1,158

OPTIONS (NOT Required)		
TFOHSS	Hydraulic Skid Shoe Kit (Dealer Install)	\$5,887
TFODDCC	Dual Drive Cross Conveyor Kit (Dealer Install)	\$4,815

PROIR YEAR OPTIONS (NOT Required)		
TFORF	Remote Filter Package (Dealer Install)	\$1,355




TF6132 TWIN-FLEX Merger
**NEW
MODEL**

- ❖ Exclusive **SOFT-SHOE™** Suspension Technology
- ❖ 32' of Continuous Working Width w/Two Heads
- ❖ ISOBUS Aux N Compatible
- ❖ Cross Conveyor Right/Left/Split/Shut-off
- ❖ Self-Contained Hydraulic System
- ❖ 65-Gallon Oil Reservoir
- ❖ Patented Center Cam/Center Drive
- ❖ Rubber-Mounted Teeth
- ❖ 42" Wide Cross Conveyor
- ❖ 385/65 x 22.5 Flotation Radial Tires
- ❖ Steering Axle
- ❖ LED Highway Lighting
- ❖ Acre Counter
- ❖ Head Height Gauge
- ❖ Hydraulic Adjust Skid Shoes
- ❖ Cat II, III, or III-N 3-Point Hitch
- ❖ Weight - 17,300#

Item #	Description	List Price
TF6132	TWIN-FLEX 32' Merger with SOFT-SHOE™ Suspension	\$209,887

PTO CHOICES (Required)

UFO1038PTO	1- ³ / ₈ " 1000 RPM Standard Length PTO	\$1,258
UFO1038LPTO	1- ³ / ₈ " 1000 RPM Long Length PTO	\$1,258
UFO1034PTO	1- ³ / ₄ " 1000 RPM Standard Length PTO	\$1,319
UFO1034LPTO	1- ³ / ₄ " 1000 RPM Long Length PTO	\$1,319

OPTIONS (NOT Required)

TFOICC	Control Box for NON-ISOBUS Tractors (<i>Dealer Installed</i>)	\$2,476
---------------	---	----------------

