

- Cuts stumps up to 45 inches in diameter
- 3-Point Mount or Skid Loader “Fast-Tach”
- Operable from Tractor or Skid Loader seat
- Oversized gear box
- Chips and debris shoot away from the operator into a heavy, reinforced rubber shield
- Comes standard with parking stand.



### **Construction and Operation:**

**3-Point Hitch Mounted StumpBusters (SC-25 & SC-50)** come with hoses and depth gauge which allows the operator to measure the depth in inches of each pass while cutting the stump. The unit utilizes an oversized shaft and heavy-duty roller bearing in an oil bath. Cylinder and cutting controls are hydraulically controlled from the tractor seat and Cat. I and II 3-Point arch support gives added stability during operation. A slip clutch located under the shield protects shear bolts and shafts from abnormally severe shock loads.

#### **SC-25 3-Point Mount**

- Requires 15-35 hp tractor
- 980 RPM cutting wheel
- Heavy duty PTO shaft
- 24 inch diameter, 3/4 inch thick cutting wheel w/ 23 carbide teeth
- Maximum cutting depth: 10 inches below ground, maximum cutting arc: 55 degrees

#### **SC-50 3-Point Mount**

- Requires 35-100 hp tractor
- 895 RPM cutting wheel
- Heavy duty PTO shaft
- 34 inch diameter, 3/4 inch thick cutting wheel w/ 25 carbide teeth
- Maximum cutting depth: 12 inches below ground, maximum cutting arc: 55 degrees

**Skid Steer Loader Mounted StumpBusters (SC-25-H, SC-30-H& SC-50-H)** feature a hydraulic motor and come equipped with hoses & quick coupler set. Mount with universal bracket only (MBS-77-10 or MBS-80-11.) Skid steer maneuverability allows the StumpBuster to eliminate dozens of stumps with no need to reposition the unit. The user has improved front-end visibility to quickly maneuver around even the biggest stumps up to 2 feet high – or clean up a whole grove in no time.

#### **SC-25-H Skid Loader Mount**

- Requires 18-25 GPM hydraulic output
- 980 RPM cutting wheel
- Fast-Tach System
- Hydraulic Motor
- 24 inch diameter, 3/4 inch thick cutting wheel w/ 23 carbide teeth
- Maximum cutting depth: 10 inches below ground, maximum cutting arc: 55 degrees

#### **SC-50-H Skid Loader Mount**

- Requires 25-40 GPM hydraulic output
- 795 RPM cutting wheel
- Fast-Tach System
- Hydraulic Motor
- 34 inch diameter, 3/4 inch thick cutting wheel w/ 25 carbide teeth
- Maximum cutting depth: 12 inches below ground, maximum cutting arc: 55 degrees

#### **SC-30-H Skid Loader Mount**

- Requires 16-30 GPM hydraulic output
- 1200 RPM cutting wheel at 25 GPM
- Fast-Tach System
- Hydraulic Motor
- 24 inch diameter, 3/4 inch thick cutting wheel w/23 carbide teeth
- Maximum cutting depth: 10 inches below ground





# STUMPBUSTER

## Optional Accessories

- **2-Spool Valve Kit** is a 2 Spool monoblock valve and is required for use with smaller tractors that come equipped with one set of hydraulics instead of the standard two sets.

## StumpBuster – Price List\*

Model	Description	Weight	List Price
SC-25	Mini StumpBuster – 3-Point Mount	832 lbs.	\$ 8,200.00
SC-25-H	Mini StumpBuster – Skid Loader Mount	834 lbs.	\$ 10,400.00
SC-30H	StumpBuster – Skid Loader Mount	650 lbs.	\$ 6,985.00
SC-50	StumpBuster – 3-Point Mount	1181 lbs.	\$ 9,450.00
SC-50-H	StumpBuster – Skid Loader Mount	1243 lbs.	\$ 11,750.00

\*All StumpBuster prices include pallet

## Optional Accessories – Price List

Model	Description	Weight	List Price
SC-2550	2-Spool Valve Kit	19 lbs.	\$ 660.00

