

POST HOLE DIGGERS

Our Post Hole Diggers Dig Deeper, Faster & Smarter

Engineered to allow the operator to dig deeper, faster and smarter, Worksaver's complete line of PTO powered diggers offer time saving convenience with outstanding reliability. Shear-bolt protected driveline is coupled to a rugged gearbox featuring tapered roller bearings and spring-loaded seals for extended service life. Large 2" output shaft has two-bolt auger connection for reliable power transfer. All job matched augers utilize fishtail center points with double flighting on the first turn for quick, positive digging action right from the start.



300 PHD shown
with optional
Parking Stand Kit

Model 300 Digger for Sub-compact Tractors

Ideal for the small acreage owners, Model 300 mates to most sub-compact tractors with a Cat. 0 or limited Cat. I three point hitches. Standard positioning handle allows the operator to place the digger from the tractor seat. Augers 30" in length are offered in 6", 9" and 12" diameters providing versatility when digging holes.

Model 500 Standard Duty Digger

Our most popular digger, the Model 500 standard duty, offers 3-position boom adjustment allowing it to adapt to most tractors. Tubular steel stock of 2.875" diameter is used for the boom for increased durability. Horseshoe yoke allows the unit to operate on Cat I/II tractors offering the operator versatility of use. Job matching augers is easy; they are 42" in length in 6", 9" and 12" diameters in single and double flight configuration. Positioning handle is standard equipment.



500 PHD

POST HOLE DIGGERS

Model 720 Heavy-duty Digger

Increased performance is offered in the Model 720 heavy-duty digger. Designed for Cat. I/II tractors, this model offers 3-position boom adjustment, rugged gearbox along with 3-1/2" diameter boom for dependable operation. Augers (42" length) are available in 6", 9", 12", 14", 18" and 24" diameters in single and double flight plus standard or heavy-duty configuration offering the outmost in productivity.



720 PHD

Post Hole Diggers Specifications

STD - Standard Duty Augers for use in lighter soils, free of stones, roots etc.

HDSF- Heavy Duty Single Flight Augers for use when encountering tougher digging conditions or where stones, roots, etc. may be present.

HDDF - Heavy Duty Double Flight Augers for use when operating in loose flowable soils such as sand/gravel, designed to help carry soil to the surface of the hole.

Model	300	500	720
Boom Size (O.D.)	2.875"	2.875"	3-1/2"
Yoke Size	1/2" x 3" HRF	3"	3"
Boom Positions	3	3	3
Mount Type	Cat. 0 (7/8" pins)	Cat. I/II	Cat. I/II
Gearbox Ratio	3:1	3:1	3.18:1
Gearbox Output Shaft	2"	2"	2"
Gearbox Bearings	Tapered Roller	Tapered Roller	Tapered Roller
Gearbox Seals	Double lip, spring loader	Double lip, spring loader	Double lip, spring loader
Drive Type	PTO, 540 RPM	PTO, 540 RPM	PTO, 540 RPM
Shear Bolt	Yes, Grade 2	Yes, Grade 2	Yes, Grade 2
Gearbox Ltd. Warranty	5-yrs.	5-yrs.	5-yrs.
Tractor hp	up to 25 hp	20 - 35 hp	25-65 hp
Hyd. Requirement	N/A	N/A	N/A
Hyd. Pressure psi	N/A	N/A	N/A
Optional Down Force Kit	N/A	Yes, DFK-50	Yes, DFK-70
Auger Sizes	6" thru 12"	6" thru 12"	6" thru 24"
Auger Length	30"	42"	42"
Auger Type	STD	STD, HDSF, HDDF	STD, HDSF, HDDF
Auger Point - Bolt-in	Fish Tail	Fish Tail	Fish Tail
12" Auger Ext.	N/A	Opt. (170705)	Opt. (170705)
Parking Stand Kit	Opt. (102160)	Opt. (102165)	Opt. (102165)
Weight (lbs.)	149	160	206
Product Number	170545	170990	706160