

DITCHERS

K

MACHINE

KIRCHNER MACHINE LTD

QUALITY BUILT EQUIPMENT

DITCHERS

DRAINAGE & IRRIGATION

K

MACHINE

3 PT & WHEEL DITCHERS

Ditches can be made with one pass , although better banks are accomplished by making two or more passes allowing tractor tires to pack the partially made banks.

- Makes new ditches up to 22" deep.
- Ideal for cleaning weedy or sodden old ditches.
- Curved wing rolls dirt up and out.
- Wing tilt adjustment with adjust-a-screw or hydraulic cylinder changes slant of banks.
- Replaceable high carbon point carves round bottom ditch.
- Replaceable cutting blades.
- Heavy duty frog and cross bracing.

3 POINT DITCHER CATEGORY II



- 3" x 8" cylinder fits into beam for more depth & more clearance (not included in price).
- Available in 6' or 7' widths.

DIGS IN & STAYS IN



- Hooks to tractor draw bar.
- Heavy 3"x 5"x 3/8" beam.
- Standard 3"x 8" cylinder controls depth (not included in price).
- Available in 6', 7' or 8' widths.
- 11' heavy duty ditcher for canals available on special order.

PULL-TYPE WHEEL DITCHER

K

MACHINE



**GENERAL
IMPLEMENT**
DISTRIBUTORS

K

MACHINE

DITCHERS

Prices Effective as of 1-22



KIRCHNER MACHINE LTD

QUALITY BUILT EQUIPMENT

MACHINE

DITCHERS

DRAINAGE & IRRIGATION



3 PT & WHEEL DITCHERS

3 POINT HITCH DITCHER



Recommended for smaller tractors

- Includes heavy duty beam with adj-a-screw for tilt,
- Does not include lift cylinder

6' 3pt. Ditcher approx. 705 lbs \$ 3750.00

7' 3pt. Ditcher approx. 765 lbs \$ 4275.00

3 PT. Ditcher Options

- Wing Tilt Cylinder - 3"x 8" Hydraulic Cylinder c/w 6 & 7' hoses (in lieu of adj-a-screw) \$ 240.00
- Lift Cylinder - when placed into 3pt beam, will lift 8" higher than 3pt hitch c/w 8 & 9' hoses \$385.00

Estimated set up time: 1/2 hour.

WHEEL DITCHER



11' WHEEL DITCHER

for canals and large main ditches

- includes 11L x 15" tires,
- 4" x 16" tilt cylinder,
- 5" x 16" lift cylinder & hoses to tractor

Special order only \$23,185.00

Estimated set up time: 2 hours

- Includes 6:70 x 15" implement tires

- Includes adj-a-screw for tilt

- Requires adj-a-screw or hydraulic cylinder for lift

6' Wheel Ditcher approx. 920 lbs \$ 5,315.00

7' Wheel Ditcher approx. 980 lbs \$ 5,840.00

8' Wheel Ditcher approx. 1090 lbs \$ 6,540.00

Wheel Ditcher Options

- Lift Cylinder 3" x 8" hydraulic cylinder w/ 6' & 7' hoses \$ 385.00
- Wing Tilt Cylinder 3" x 8" hydraulic cylinder /w 12' & 13' hoses (in lieu of adj-a-screw) \$ 320.00
- Coulter Assembly cuts grass, straw or sloughs, helps to eliminate plugging \$ 425.00



MACHINE

GENERAL IMPLEMENT DISTRIBUTORS



MACHINE