



Power Landscape Rakes are the ideal tool for the landscape contractor, large property owner, rental yard, park & recreation department or turf management professional. They do it all, prep, smooth, set grade, level, till, remove rocks and create the perfect seedbed.



Carbide Rotor

- Quick-flip side shields are self-storing on the unit allowing ease of windrowing rocks or debris
- Durable triple sealed bearings with bearing protectors for long service life
- Time saving replaceable rotor bearing assemblies
- Choice of rotors 2" Sabre Tooth or 1-3/4" Carbide Tooth
- Auto adjust chain tensioner is standard on all models



Sabre Rotor









10-Series Powered Landscape Rakes

Elevating productivity, the 10-Series Power Rakes for Mini / Compact Skid Steers features a #80 chain drive, flip-up side shields, dual gauge wheels, adjustable material bar and optional hydraulic angle.

As with all Power Rakes, bearing protectors and environmentally friendly dry chain case are standard equipment.

SPECIFICATIONS -10 Se	ries for Mini Ski	d Steers w/Universa	Mount – * Mounts	for Bobcat MT & G	ehl available	
Model	PXS-410	PXS-510	PXS-610	PXS-410ST	PXS-510ST	PXS-610ST
Mount Type	Mini-SS	Mini-SS	Mini-SS	Mini-SS	Mini-SS	Mini-SS
Main Frame (in)	3 x 3 x 3/16					
Overall Width (in/cm)	56/142	68/173	80/203	56/142	68/173	80/203
Working Width (in/cm)	48/122	60/152	72/183	48/122	60/152	72/183
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R					
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Rotor Drive	#80 Roller Chain					
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	Carbide
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	524/238	560/254	596/270	526/239	562/255	598/271
Product No.	360600	360605	360610	360615	360620	360625





20-Series Powered Landscape Rakes

Responsive and reliable, the 20-Series is designed for Skid Steers up to 65 HP. Features a #80 chain drive, dual flip-up gauge wheels, flip-up side shields and an all-welded frame constructed of 3" x 4" x 1/4" tubing.

Also standard are reliable gauge wheels (16 x 6.50-8) mounted to 4-bolt hubs and a "Flex & Float" System offering the operator flexibility to choose maximum down pressure or float position for site prep.



SPECIFICATIONS – 20-Series for Skid Steers under 65 HP								
Model	PSS-620	PSS-720	PSS-620ST	PSS-720ST				
Mount Type	Skid Steer	Skid Steer	Skid Steer	Skid Steer				
Main Frame (in)	3 x 4 x 1/4							
Overall Width (in/cm)	80/203	92/234	80/203	92/234				
Working Width (in/cm)	72/183	84/214	72/183	84/214				
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8				
Max. Angle	20° L/R	20° L/R	20° L/R	20° L/R				
Hydraulic Angle	Optional	Optional	Optional	Optional				
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic				
Rotor Drive	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain	#80 Roller Chain				
Chain Tensioner	Standard	Standard	Standard	Standard				
Rotor Tooth	Carbide	Carbide	2" Sabre	2" Sabre				
Gauge Wheel	Dual	Dual	Dual	Dual				
Flip-up Side Shields	Standard	Standard	Standard	Standard				
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable				
Weight (lbs/kg)	830/376	866/393	832/377	868/394				
Product No.	360850	360855	360860	360865				

65-Series Powered Landscape Rakes

Consistently delivering high performance, the 65-Series is designed for Skid Steers over 65 HP. It's rugged $4" \times 4" \times 1/4"$ frame supports dual flip-up gauge wheels (18.5 x 8.50-8) on 5-bolt hubs, flip-up side shields, adjustable material bar and environmentally dry chain case. A double #80 chain transfers the power to the rotor while chain tensioners of UMHW material provides the correct tension.

SPECIFICATIONS - 65-Se	eries for Skid Ste	ers over 65 HP				
Model	PSHD-665	PSHD-765	PSHD-865	PSHD-665ST	PSHD-765ST	PSHD-865ST
Mount Type	Skid Steer					
Main Frame (in)	4 x 4 x 1/4					
Overall Width (in/cm)	80/203	92/234	104/264	80/203	92/234	104/264
Working Width (in/cm)	72/183	84/214	96/244	72/183	84/214	96/244
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R					
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Rotor Drive	#80 Double Roller Chain					
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2″ Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	1060/481	1105/501	1145/519	1062/482	1107/502	1147/520
Product No.	360570	360575	360580	360585	360590	360595





25-Series Powered Landscape Rakes

Get more done with a compact tractor when using one of our 25-Series Power Rakes designed for tractors of 24-40 HP. Standard equipment includes a #80 drive chain for dependable power transfer, PTO with slip clutch, dual flip-up gauge wheels, flip-up side shields for easy storage on the machine and adjustable material bar for controlling processed material flow.

SPECIFICATIONS – 25-Series for Tractors 24-40 HP								
Model	PTC-525	PTC-625	PTC-725	PTC-525ST	PTC-625ST	PTC-725ST		
Mount Type	3-pt Cat. I							
Main Frame (in)	3 x 3 x 3/16							
Overall Width (in/cm)	68/173	80/203	92/234	68/173	80/203	92/234		
Working Width (in/cm)	60/152	72/183	84/214	60/152	72/183	84/214		
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8		
Max. Angle	20° L/R							
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional		
Drive System	PTO	PTO	PTO	PTO	PTO	PTO		
Rotor Drive	#80 Roller Chain							
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard		
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	2" Sabre		
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual		
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard		
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable		
Weight (lbs/kg)	755/343	790/358	825/374	757/343	792/359	827/375		
Product No.	360800	360805	360810	360815	360820	360825		

40-Series Powered Landscape Rakes

Providing ingenious solutions for your site prep needs, the 40-Series 3-pt mounted Power Rakes are matched to tractors of 35-75 HP. Standard features include PTO with slip clutch for sure power transfer, double #80 chain drive for long service life, rugged $4" \times 4" \times 1/4"$ frame, dual flip-up gauge wheel on 5-bolt hubs and heavy-duty adjustable material bar to control processed material flow.



SPECIFICATIONS - 40-Se	eries for Tractors	35-75 HP				
Model	PTHD-640	PTHD-740	PTHD-840	PTHD-640ST	PTHD-740ST	PTHD-840ST
Mount Type	3-pt Cat II					
Main Frame	4 x 4 x 1/4					
Overall Width (in/cm)	80/203	92/234	104/264	80/203	92/234	104/264
Working Width (in/cm)	72/183	84/214	96/244	72/183	84/214	96/244
Working Depth (in/cm)	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8	0-3.0/0-8
Max. Angle	20° L/R					
Hydraulic Angle	Optional	Optional	Optional	Optional	Optional	Optional
Drive System	PTO	PTO	PTO	PTO	PTO	PTO
Rotor Drive	#80 Double Roller Chain					
Chain Tensioner	Standard	Standard	Standard	Standard	Standard	Standard
Rotor Tooth	Carbide	Carbide	Carbide	2" Sabre	2" Sabre	2" Sabre
Gauge Wheel	Dual	Dual	Dual	Dual	Dual	Dual
Flip-up Side Shields	Standard	Standard	Standard	Standard	Standard	Standard
Material Control Bar	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Weight (lbs/kg)	1065/483	1160/526	1255/569	1068/484	1162/527	1257/570
Product No.	360870	360875	360880	360885	360890	360895





Power Rake Features

Flip-up Gauge Wheels (height adjustable) – Allows accurate control of working depth, keeping machine level for smoother surface finish. Operator can easily move the gauge wheels into the up position for transport on a trailer, reducing the space needed.

Flip-up Side Shields – Operator can easily move the shield out of the way for work where shields are not required. Shields are always with the machine, reducing the chance of misplacement.

Rotor Choice – Available with a carbide aggressor tooth (1-3/4") or 2" Sabre tooth (heat treated alloy material). Sabre tooth offers excellent reliability and performance for general use. Aggressor tooth offers more aggressive tilling action.

Dry Chain Case – Environmentally friendly dry chain case reduces maintenance as there is no oil to contend with. Chain only requires lubrication every 15-20 hours and is simply done by removing the chain case cover.

Heavy-Duty Chain – Chain is #60, #80 or double #80 depending on model. Chain size is matched to the machine for maximum power transfer. Tension is provided by serviceable chain tensioners of UMHW material for longer wear and reliability.

Adjustable Material Bar – Standard on all models for controlling processed material flow. Allows the operator to adjust to soil conditions increasing versatility of the unit.

Triple Seal Rotor Bearing with Replaceable Housing –Bearing housing of ductile material is replaceable, extending the life of the machine. Triple seal bearing keeps dirt out, providing more uptime.

Bearing Protectors – Standard on both sides of bearing on non-drive-end, or on rotor side of bearing on drive-end. Protects bearings from wrapping with material, thus increasing the service life of the bearings.

Lifting Point – Built-in lifting hook is standard on all machines for easier loading / unloading of machine.

Flex & Float System – Skid Steer units feature a "Flex & Float" mount. Allows the operator the flexibility to choose maximum down pressure for preliminary site prep, then switch to float position for final site preparation.







Designed for Use on Mini / Compact Skid Steers.

Hydraulically Driven 10-Series, Standard Equipment includes, #80 Chain Drive, Flip-up Side Shields, 3"x 3"x 3/16" Frame, Two Flip-up Gauge Wheels, Adjustable Material Bar, hydraulic hoses w/ connect under pressure couplers

Product	Model	Item #	Description	Lbs.	List
	PXS-410	360600	4-ft Powered Landscape rake with Universal "mini" skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	524	11,004.00
	PXS-510	360605	5-ft Powered Landscape rake with Universal "mini" skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	560	11,767.00
	PXS-610	360610	6-ft Powered Landscape rake with Universal "mini" skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	596	12,705.00
	PXS-410-ST	360615	4-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal "mini" Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/ couplers std.	526	10,234.00
	PXS-510-ST	360620	5-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal "mini" Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/ couplers std.	562	10,976.00
	PXS-610-ST	360625	6-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal "mini" Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/ couplers std.	598	11,893.00







		Options		•
Side Shield Extensions	360375	Pair of Extensions mounts to side shield, for Model PXS-series		196.00
Hyd. Angle kit	360635	Hydraulic angle kit for 10-series includes cylinder & hoses allowing use on power units with two sets of remotes.	22	616.00
Hyd. Angle Kit w/ solenoid	360640	Hydraulic angle kit with solenoid for 10- series, includes cylinder & hoses allowing use on power units with only one remote	36	1,484.00
Powered Lands	cape Rake	with alterative Mounts for 10-Series Mach	nines.	
			1	
	360700	PXS-410 with Bobcat MT Mount	540	11,312.00
	360705	PXS-510 with Bobcat MT Mount	576	12,082.00
Bobcat	360715	PXS-610 with Bobcat MT Mount	612	13,027.00
Mount	360720	PXS-410ST with Bobcat MT Mount	542	10,549.00
	360725	PXS-510ST with Bobcat MT Mount	578	11,284.00
	300723	1118 51081 Willi Bootat Will Wieamt	- , -	11,201.00





Designed for Use on Skid Steers under 65 hp.

Hydraulically Driven, Standard Equipment includes, #80 Chain Drive, Flip-up Side Shields, 3" x 4" x 1/4" Frame, Two Flip-up Gauge Wheels, Adjustable Material Bar, Hydraulic hoses w/ connect under pressure couplers, Universal Skid Steer Mount

Product	Model	Item #	Description	Lbs.	List
	PSS-620	360850	6-ft Powered Landscape rake with Universal skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	830	12,397.00
	PSS-720	360855	7-ft Powered Landscape rake with Universal skid steer mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	866	13,321.00
	PSS-620-ST	360860	6-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/couplers	832	11,571.00
	PSS-720-ST	360865	7-ft Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hoses w/couplers	868	12,516.00
			Options		
	Side Shield Extensions	360985	Pair of Extensions, mounts to side shield, for Model PSS-series	18	196.00
	Hyd. Angle Kit w/ Solenoid	360779	Hydraulic angle kit with solenoid for PSS- Series, includes cylinder & hoses allowing use on power units with only one remote	36	2,135.00

Electrical Wiring Kits for Skid Steers

To connect our electric / hydraulic solenoid control when installed on our Powered Rakes into OEM Skid Steer auxiliary electric controls allowing operating the electric / hydraulic solenoid valve from the operator seat with the buttons on the hand control.







Heavy-Duty Design for Use on Skid Steers over 65 hp.

Hydraulically Driven, Standard Equipment includes, Double #80 Chain Drive, Flip-up Side Shields, 4" x 4" x 1/4" Frame, Two Flip-up Gauge Wheels, Adjustable Material Bar, Hydraulic hoses w/ connect under pressure couplers, Universal Skid Steer Mount

Product	Model	Item #	Description	Lbs.	List
	PSHD-665	360570	6-ft HD-Powered Landscape rake with Universal skid steer mount, manual angle (3- position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	1060	14,203.00
	PSHD-765	360575	7-ft HD- Powered Landscape rake with Universal skid steer mount, manual angle (3- position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	1105	14,959.00
	PSHD-865	360580	8-ft HD- Powered Landscape rake with Universal skid steer mount, manual angle (3- position), Carbide Aggressor rotor, side shields & two gauge wheels, hoses w/couplers	1145	16,086.00
	PSHD-665-ST	360585	6-ft HD- Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3- position). Side shields & two gauge wheels, hose w/couplers	1065	13,384.00
	PSHD-765-ST	360590	7-ft HD-Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hose w/couplers	1105	14,126.00
	PSHD-865-ST	360595	8-ft HD-Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Universal Skid Steer mount. Manual angle (3-position). Side shields & two gauge wheels, hose w/couplers	1145	15,141.00
			Options		
	Side Shield Extensions	360985	Pair of Skid Shoes Mounts to side shield, for Model PSHD-series	18	196.00
	Hyd. Angle Kit w/ Solenoid	360864	Hyd. angle kit w/ solenoid for PSHD-Series (6' / 7'), includes cylinder & hoses use on power units with only one remote	59	2,135.00
	Hyd. Angle Kit w/ Solenoid	360866	Hyd. angle kit w/ solenoid for PSHD-Series (8'), includes cylinder & hoses use on power units with only one remote	60	2,135.00

Electrical Wiring Kits for Skid Steers

To connect our electric / hydraulic solenoid control when installed on our Powered Rakes into OEM Skid Steer auxiliary electric controls allowing operating the electric / hydraulic solenoid valve from the operator seat with the buttons on the hand control.





PTO Driven for Use on Tractors, 24 – 40 hp

PTO Driven (540 rpm), Standard Equipment includes, PTO w/ Slip Clutch, #80 Chain Drive, Flip-up Side Shields, Two Flip-up Gauge Wheels, Adjustable Material Bar, Manual Angle.

Fits Category I 3-pt

Product	Model	Item #	Description	Lbs.	List
	PTC-525	360800	5-ft PTO Powered Landscape rake 3-pt mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, slip clutch	755	11,305.00
	PTC-625	360805	6-ft PTO Powered Landscape rake 3-pt mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, slip clutch	790	12,075.00
	PTC-725	360810	7-ft PTO Powered Landscape rake 3-pt mount, manual angle (3-position), Carbide Aggressor rotor, side shields & two gauge wheels, slip clutch	825	13,006.00
	PTC-525-ST	360815	5-ft PTO Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Manual angle (3-position). Side shields & two gauge wheel, slip clutch	757	10,500.00
	PTC-625-ST	360820	6-ft PTO Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Manual angle (3-position). Side shields & two gauge wheels, slip clutch	792	11,249.00
	PTC-725-ST	360825	7-ft PTO Powered Landscape rake with Sabre Tooth rotor (2" composite metal tooth) Manual angle (3-position). Side shields & two gauge wheels, slip clutch	827	11,907.00
			Options		
	Side Shield Extension	360985	Pair of Extensions Mounts to side shield, for Model PTC / PTHD-series	18	196.00
	Hyd. Angle Kit	360915	Hydraulic angle kit for PTC models, includes cylinder & hoses less couplers		532.00







Heavy Duty Design for PTO Driven for Use on Tractors, 35-75 hp

PTO Driven (540 rpm), Standard Equipment includes, PTO w/ Slip Clutch, Double #80 Chain Drive, 4" x 4" x 1/4" Frame, Flip-up Side Shields, Two Flip-up Gauge Wheels, Adjustable Material Bar, Manual Angle.

Fits Category I / II 3-pt

Product	Model	Item #	Description	Lbs.	List
			6-ft PTO Powered Landscape rake		
			3-pt mount, manual angle (3-position),		
	PTHD-640	360870	Carbide Aggressor rotor, side shields & two	1065	14,357.00
			gauge wheels, slip clutch		
			7-ft PTO Powered Landscape rake		
			3-pt mount, manual angle (3-position),		
	PTHD-740	360875	Carbide Aggressor rotor, side shields & two	1160	15,253.00
			gauge wheels, slip clutch		
			8-ft PTO Powered Landscape rake		
			3-pt mount, manual angle (3-position),		
	PTHD-840	360880	Carbide Aggressor rotor, side shields & two	1255	16,142.00
			gauge wheels, slip clutch		
			6-ft PTO Powered Landscape rake with		
	PTHD-640-ST	360885	Sabre Tooth rotor (2" composite metal	1068	13,552.00
			tooth) Manual angle (3-position). Side		
			shields & two gauge wheel, slip clutch		
			7-ft PTO Powered Landscape rake with		
	PTHD-740-ST	360890	Sabre Tooth rotor (2" composite metal	1162	14,462.00
			tooth) Manual angle (3-position). Side		
			shields & two gauge wheels, slip clutch		
			8-ft PTO Powered Landscape rake with		
	PTHD-840-ST	360895	Sabre Tooth rotor (2" composite metal	1257	15,232.00
			tooth) Manual angle (3-position). Side		
			shields & two gauge wheels, slip clutch		
		2 6000 -	Options	4.0	10600
	Side Shield	360985	Pair of Extensions Mounts to side shield, for	18	196.00
	Extension	260005	Model PTC / PTHD-series		=25 22
	Hyd. Angle	360905	Hydraulic angle kit for PTHD models,		532.00
	Kit		includes cylinder & hoses less couplers		



