

**Worksaver**




# Rugged Rear Blades — for the Tough Jobs!

## Rear Blade Options

### Skid Shoes

- Remove Snow
- Level Gravel
- Clean Feedlots or Barns
- Reduce Blade Damage
- Increase Blade Life
- Prevent Gouging




Snow removal and farm cleanup have fewer surprises when skid shoes are attached to the rear blade. No more guessing blade height each time you lower the blade. Skid shoes provide adjustable clearance to travel over uneven surfaces that can damage the blade. They also help prevent damage to the blade when used in cleaning level surfaces, simplifying operations on drive-ways, barn floors and feedlots.

#### SKID SHOES FOR REAR BLADES

Model	SK-5	SK-8
Number	343435	346745
Used On	MCRB/RB Series	RBHD Series

### End Plates



Material handling is easier when you install rear blade end plates. Quickly gather and efficiently move dirt, gravel, slurry or manure to more desirable locations.

#### END PLATES FOR REAR BLADES

Model	EP-40
Number	346765
Used On	RBHD Series
Weight	44 lbs.

Simple yet rugged design is used in these value-priced blades. Designed for tractors up to 25 hp, the DC-Series offers mechanical angle adjustment only. The moldboard utilizes a 3/8" x 3" welded cutting edge. An all-welded A-frame is matched to the blades horsepower requirements. Shipped with 7/8" Cat. 1 pins (5/8" Cat. 0 pins available).

## DC-Series Blades



	DC-4	DC-5
Item No.	345600	345500
Maximum hp	25 hp	25 hp
Frame Size	3" x 1.5"	3" x 1.5"
A-Frame	Formed Channel	Formed Channel
3-pt. Hitch	Welded Straps	Welded Straps
Moldboard Width	Cat. 0/1	Cat. 0/1
Moldboard Height	4'	5'
Moldboard Thickness	10"	10"
Cutting Edge — Welded	3/16"	3/16"
Angle/Pivot	3/8" x 3"	3/8" x 3"
Angle Forward (degrees)	360°	360°
Angle Reverse (degrees)	0, 15, 30	0, 15, 30
Offset	0, 15, 30	0, 15, 30
Tilt	N/A	N/A
Parking Stand	N/A	N/A
Weight	N/A	N/A
	114 lbs.	126 lbs.



## MCRB-72

An economical 6' blade for tractors up to 35 hp, with Cat. I 3-pt. hitch. The MCRB-72 only offers mechanical angle adjustment. The main frame is formed with 3" x 2.5" channel; replaceable straps are used for the A-frame. The formed moldboard includes a 1/2" x 6" reversible cutting edge.

MCRB-72	
Item No.	346775
Maximum hp	35 hp
Frame Size	3" x 2.5"
A-Frame	Formed Channel
3-pt. Hitch	Bolted Straps
Moldboard Width	Cat. I
Moldboard Height	6'
Moldboard Thickness	12"
Cutting Edge — Reversible	1/4"
Angle/Pivot	1/2" x 6"
Angle Forward (degrees)	360°
Angle Reverse (degrees)	0, 15, 30
Offset	0, 15
Tilt	N/A
Parking Stand	N/A
Weight	N/A
	186 lbs.
Optional Item	
SK-5 Skid Shoes	Yes




## RB-Series Standard Rear Blades

	RB-1272	RB-1284
<b>Item No.</b>	346705	346715
<b>Maximum hp</b>	40 hp	40 hp
<b>Frame Size</b>	3" x 3"	3" x 3"
<b>A-Frame</b>	Welded Mast	Welded Mast
<b>3-pt. Hitch</b>	Cat. I	Cat. I
<b>Moldboard Width</b>	6'	7'
<b>Moldboard Height</b>	12"	12"
<b>Moldboard Thickness</b>	1/4"	1/4"
<b>Cutting Edge — Reversible</b>	1/2" x 6"	1/2" x 6"
<b>Angle/Pivot</b>	360°	360°
<b>Angle Forward (degrees)</b>	0, 15, 30	0, 15, 30
<b>Angle Reverse (degrees)</b>	0, 15	0, 15
<b>Offset</b>	12" R/L	12" R/L
<b>Tilt</b>	N/A	N/A
<b>Parking Stand</b>	Standard	Standard
<b>Weight</b>	190 lbs.	206 lbs.
<b>Optional Item</b>		
<b>SK-5 Skid Shoes</b>	Yes	Yes

Designed for Cat. I or Cat. I Quick Hitch these standard duty blades are ideal for the small acreage owner. The main frame consist of an all welded mast and 3" x 3" square tubing. The RB-Series features mechanical offset and angle adjustment. Angle adjustment is done by simply removing a pin, angling the blade and reinstalling the pin. All models have a reversible cutting edge and are supplied with a parking stand for convenient storage. Available as an option are skid shoes to assist in cutting height adjustment to reduce the chance of surface damage during snow removal.





## RBHD-Series Heavy Duty Rear Blades



Designed for Cat. I or Cat. I Quick Hitch these heavy-duty models have the strength required to handle the tough jobs. The main frame consist of an all welded mast and 4" x 4" square tubing. The RBHD-Series features mechanical offset and angle adjustment. Angle adjustment is done by simply removing a pin, angling the blade and reinstalling the pin. The RBHD-6-T and RBHD-7-T utilize a 3-position tilt assembly that is easy to use. All models have a reversible cutting edge and are supplied with a parking stand for convenient storage. Available options are skid shoes to assist in cutting height adjustment to reduce the chance of surface damage during snow removal. Optional end plates provide a boxed area for grading.

	RBHD-6	RBHD-7	RBHD-6-T	RBHD-7-T
<b>Item No.</b>	346780	346785	346790	346795
<b>Maximum hp</b>	50 hp	50 hp	50 hp	50 hp
<b>Frame Size</b>	4" x 4"	4" x 4"	4" x 4"	4" x 4"
<b>A-Frame</b>	Welded Mast	Welded Mast	Welded Mast	Welded Mast
<b>3-pt. Hitch</b>	Cat. I	Cat. I	Cat. I	Cat. I
<b>Moldboard Width</b>	6'	7'	6'	7'
<b>Moldboard Height</b>	14"	14"	14"	14"
<b>Moldboard Thickness</b>	1/4"	1/4"	1/4"	1/4"
<b>Cutting Edge — Reversible</b>	1/2" x 6"	1/2" x 6"	1/2" x 6"	1/2" x 6"
<b>Angle/Pivot</b>	360°	360°	360°	360°
<b>Angle Forward (degrees)</b>	0, 15, 30	0, 15, 30	0, 15, 30	0, 15, 30
<b>Angle Reverse (degrees)</b>	0, 15	0, 15	0, 15	0, 15
<b>Offset</b>	12" R/L	12" R/L	12" R/L	12" R/L
<b>Tilt</b>	N/A	N/A	3-position	3-position
<b>Parking Stand</b>	Standard	Standard	Standard	Standard
<b>Weight</b>	275 lbs.	299 lbs.	288 lbs.	309 lbs.
<b>Optional Items</b>				
<b>SK-8 Skid Shoes</b>	Yes	Yes	Yes	Yes
<b>EP-40 End Plates</b>	Yes	Yes	Yes	Yes

### Acreage Attachments

<b>Tractor 3-pt. Mounted Rear Blades</b>					
<b>Product</b>	<b>Model</b>	<b>Item #</b>	<b>Description</b>	<b>Lbs.</b>	<b>List</b>
	<b>MCRB-72</b>	346775	6-ft Economy Rear Blade for 3-pt Hitch Cat. I with 7/8" pins. Moldboard height is 12" with reversible 6" cutting edge. For Tractors up to 35 hp	185	826.00
	<b>RB-1272</b>	346705	6-ft Standard-duty Rear Blade for 3-pt hitch. Cat. I (7/8" pins), Quick Hitch Compatible. Moldboard height is 12" 1/2" x 6" cutting edge. For Tractors up to 40 hp	190	931.00
	<b>RB-1284</b>	346715	7-ft Standard-duty Rear Blade for 3-pt hitch. Cat. I (7/8" pins), Quick Hitch Compatible. Moldboard height is 12" 1/2" x 6" cutting edge. For Tractors up to 40 hp	206	1,001.00
<b>RBHD Blades are Cat. I Quick Hitch Compatible. Includes Parking Stand</b>					
	<b>RBHD-6</b>	346780	6-ft Utility Rear Blade with offset for 3-pt hitch. Cat. I (7/8" pins), Quick Hitch Compatible. Moldboard height 14" Bolt-on 1/2" x 6" cutting edge. For Tractors up to 50 hp	275	1,176.00
	<b>RBHD-7</b>	346785	7-ft Utility Rear Blade with offset for 3-pt hitch. Cat. I (7/8" pins), Quick Hitch Compatible. Moldboard height 14" Bolt-on 1/2" x 6" cutting edge. For Tractors up to 50 hp	300	1,211.00
	<b>RBHD-6-T</b>	346790	6-ft Utility Rear Blade with offset / tilt for 3-pt hitch. Cat. I (7/8" pins), Quick Hitch Compatible. Moldboard height 14" Bolt-on 1/2" x 6" cutting edge For Tractors up to 50 hp	306	1,407.00
	<b>RBHD-7-T</b>	346795	7-ft Utility Rear Blade with offset / tilt for 3-pt hitch. Cat. I (7/8" pins), Quick Hitch Compatible. Moldboard height 14" Bolt-on 1/2" x 6" cutting edge For Tractors up to 50 hp	331	1,477.00
	<b>SK-5</b>	343435	Skid Shoes for RB & MCRB series only (pair)	9	98.00
	<b>SK-8</b>	346745	Skid Shoes for RBHD and older URB / UB series only (pair)	24	371.00
	<b>EP-40</b>	346765	End Plates for RBHD series only (pair)	44	329.00