

The widest choice of quality land management attachments.





Rotary Brooms

Designed for use by contractors, municipalities, institutions and farmers. Hydraulically driven models for skid steers, PTO driven models for 3-pt. tractor mounts (Cat.I). 32 inch diameter convoluted brushes available in Poly (P) or both Poly and Wire (PW). All models available in 5-ft., 6-ft., & 7-ft. widths.

- Remove dirt, sand, gravel and trash from construction entrances, parking lots, bridges, driveways & sidewalks.
- Remove thatch and prepare turf for the growing season.
- Clean snow or leaves from streets, driveways, and building entrances.
- Excellent for general clean up before sealing or repairing pavement.
- Brooms angle up to 30-degrees right or left. Optional manual or hydraulic angle adjustment kits available.
- Height adjustment chains maintain an even operating position.
- Parking stand included as standard equipment.

Skid Steer Rotary Broom

- Hydraulically driven skid steer models in 5-ft., 6-ft.,
 7-ft.widths with 32" diameter brushes.
- Variable flow control valve for optimum broom speed.
- Step-through mount design for easy in/out of skid steer cab.
- · Optional electric solenoid kit also offered.
- 4.36/1 chain drive ratio provides job matched torque to get through tough conditions.

3-pt. Rotary Broom

- PTO driven 3-pt. tractor mount in 5-ft., 6-ft., & 7-ft. widths with 32" diameter brushes.
- Double gearbox drive with patented top "T-shaft" for smooth power transmission and easy reversal of brush rotation.
- Designed for Category I tractors with 1,000 lbs. or greater 3-pt. lift capacity.



Skid Steer Rotary Broom Specifications

	SSMB-325P	SSMB-325PW	SSMB-326P	SSMB-326PW	SSMB-327P	SSMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	Skid Steer					
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
Hydraulic Motor Rating	16 GPM					
Oil Flow Requirement (gpm/lpm)	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114	12-30 / 45-114
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	640 / 290	637 / 289	740 / 336	736 / 334	840 / 381	833 / 378
Product No.	610961	610960	610966	610965	610971	610970



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

3-pt. Rotary Broom Specifications

	RMB-325P	RMB-325PW	RMB-326P	RMB-326PW	RMB-327P	RMB-327PW
Overall Width (in/cm)	69 / 175	69 / 175	81 / 206	81 / 206	93 / 236	93 / 236
Brush Diameter (in/cm)	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	60 / 152	72 / 183	72 / 183	84 / 213	84 / 213
Width @ 30° Angle (in/cm)	53 / 135	53 / 135	64 / 163	64 / 163	76 / 193	76 / 193
Mounting System	3-pt. (Cat. I)					
Brush Material	Poly	Poly / Wire	Poly	Poly / Wire	Poly	Poly / Wire
PTO RPM Range	540	540	540	540	540	540
Dirt Deflector	Optional	Optional	Optional	Optional	Optional	Optional
Weight (lbs/kg)	720 / 326	714 / 324	780 / 354	774 / 351	840 / 381	833 / 378
Product No.	610705	610700	610755	610750	610805	610800



WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.

Options

	Angle Adjustments Kits (all models require either a manual or hydraulic kit)
Product No. 610702	Manual Angle Adjustment Kit for either skid steers or 3-pt. tractor.
Product No. 610703	3-pt. Hydraulic Angle Adjustment Kit – includes cylinder & hoses less tips.
Product No. 610704	Skid Steer Hydraulic Angle Adjustment Kit – includes electric hydraulic solenoid control valve. For skid steer brooms used on units with only one set of remotes. Includes cylinder, hoses, valve, & flat-faced couplers. Factory installed.
	Electric Solenoid Kit (Optional)
Product No. 610950	Field installed electric hydraulic solenoid valve kit – fits product no. #610703 hydraulic angle kit above.





Land Management Attachments

Rotary Brooms

Brooms angle 30-degrees right or left, and height adjustment chains maintain even operating position. Available in 32" diameter poly (P) or poly/wire (PW) combination. Parking stand standard. Either manual or hydraulic angle adjustment kit is required.

	Either manual or hydraulic angle adjustment kit is required.						
NOTE: For c	NOTE: For complete broom assembly, choose broom from Group I, and kit from Group 2 below.						
	Group 1 – Base Broom 3-pt Mount						
			en Double Gearbox Drive				
Product	Model	Item #	Description	Lbs.	List		
	RMB-325P	610705	5-ft. Wide Poly Broom. Angle kit req.		7 (72 00		
			Cat. I Quick Hitch compatible.	640	7,672.00		
	RMB-325PW	610700	5-ft. Wide Poly / Wire Broom. Angle				
			kit req. Cat. I Quick Hitch compatible.	637	7,672.00		
			6-ft. Wide Poly Broom. Angle kit req.		0.042.00		
	RMB-326P	610755	Cat. I Quick Hitch compatible.	740	8,043.00		
* 7			6-ft. Wide Poly / Wire Broom. Angle				
	RMB-326PW	610750	kit req. Cat. I Quick Hitch compatible	736	8,043.00		
			7-ft. Wide Poly Broom. Angle kit req.				
	RMB-327P	610805	Cat. I Quick Hitch compatible.	840	8,771.00		
			7-ft. Wide Poly / Wire Broom. Angle				
	RMB-327PW	610800	kit req. Cat. I Quick Hitch compatible	833	8,771.00		
			Steer Mount Hydraulic Drive				
			paders that utilize the "universal" skid steen				
Either manual or hydraulic angle adjustment kit is required. Optional gauge wheel kit is recommended.							
	SSMB-325P	610961	5-ft. Wide Poly Broom. Angle kit req.	720	8,218.00		
	SSMB-325PW	610960	5-ft. Wide Poly / Wire Broom.				
			Angle kit required.	714	8,218.00		
	SSMB-326P	610966	6-ft. Wide Poly Broom. Angle kit req.	780	8,750.00		
	SSMB-326PW	610965	6-ft. Wide Poly / Wire Broom.				
			Angle kit required.	774	8,750.00		
	SSMB-327P	610971	7-ft. Wide Poly Broom. Angle kit req.	840	9,653.00		
			7-ft. Wide Poly / Wire Broom.				
	SSMB-327PW	610970	Angle kit required.	833	9,653.00		
			Gauge wheel kit allows setting the				
	Opt. Gauge	610665	broom height to match		616.00		
	Wheel Kit		the job conditions.				
			Minimizing brush to ground contact.				
Group 2 – Angle Adjustment Kit							
Item #			Description	Lbs.	List		
610702	Manual Angle Adjustment Kit		6	203.00			
610703			nt Kit. Includes cylinder, hoses less tips.		637.00		
	For use on tractor mounted 3-pt units.						

GENERAL
IMPLEMENT
HAIPEEIAIEIGI
DISTRIBUTORS



Land Management Attachments

			Rotary Brooms			
Universa	ıl Front Loader hvo		driven brooms. Requires interfacing mounti	ing brackets		
			oly/wire (PW) combination. Either manual			
1			Optional gauge wheel kit is recommended.			
No	3		oose broom from Group 1 & Kit from Gr			
Grou	p 1 - Front Loade	r Mount (1	requires additional brackets) (shipped le	ss noses)		
			5-ft Universal front loader Poly Broom.			
	ULMB-325P	610605	Shipped less Brts. Optional bolt-on brackets available (pgs. 57-71)	7,721.00		
			Angle kit required			
			5-ft Universal front loader Poly/Wire			
	ULMB-325PW	610610	Broom. Shipped less Brts. Optional bolt-on	7,721.00		
			brackets available (pgs. 57-71)			
			Angle kit req.			
			6-ft Universal front loader Poly Broom.			
	ULMB-326P	610615	Shipped less Brts. Optional bolt-on brackets available (pgs. 57-71)	8,260.00		
			Angle kit required			
			6-ft Universal front loader Poly/Wire			
			I			
	ULMB-326PW	610620	Broom. Shipped less Brts. Optional bolt-on brackets available (pgs. 57-71)	8,260.00		
			Angle kit required			
			7-ft Universal front loader Poly Broom.			
		-10- - -	I -	2.4.5.00		
	ULMB-327P	610625	Shipped less Brts. Optional bolt-on brackets available (pgs. 57-71)	9,156.00		
			Angle kit required			
			7-ft Universal front loader Poly/Wire			
	LILAID 227DW	(10(20	_	0.156.00		
	ULMB-327PW	610630	Broom. Shipped less Brts. Optional bolt-on brackets available (pgs. 57-71)	9,156.00		
			Angle kit required			
Gr	oun 1 -John Deer	e 400/500 s		hoses)		
Group 1 -John Deere 400/500 series loader mount broom (shipped less hoses) Available in 32" poly (P) or poly/wire (PW) combination. Either manual or hydraulic angle adjustment kit						
			eel kit is recommended. (Group 2 kit requi			
18	JDMB-325P	610635	5-ft Poly Broom for John Deere 400/500	8,267.00		
	JDMB-323P	010033	series loader. Angle kit req.	8,207.00		
	JDMB-325PW	610640	5-ft Poly/Wire Broom for John Deere	8,267.00		
	JDMD-323F W	010040	400/500 series loader. Angle kit req.	8,207.00		
	JDMB-326P	610645	6-ft Poly Broom for John Deere 400/500	8,792.00		
	JDMD-320P	010043	series loader. Angle kit req.	8,792.00		
	JDMB-326PW	610650	6-ft Poly/Wire Broom for John Deere	8,792.00		
	JDMD-320F W	010030	400/500 series loader. Angle kit req.	0,792.00		
	JDMB-327P	610655	7-ft Poly Broom for John Deere 400/500	9,695.00		
	JDMD-32/F	010055	series loader. Angle kit req.	9,093.00		
	JDMB-327PW	610660	7-ft Poly/Wire Broom for John Deere	9,695.00		
	3DMD-32/FW	010000	400/500 series loader. Angle kit req.	9,093.00		
			Recommended for front loader brooms.			
	Ont Carra	610665	Gauge wheel kit allows setting the broom	616.00		
	Opt. Gauge	610665	height to match the job conditions.	616.00		
	Wheel Kit		Minimizing brush to ground contact			
Note:	All broom prices i	nclude a wa		d 2-high		
11016.	Note: All broom prices include a well-built crate and can be stacked and shipped 2-high.					





Land Management Attachments

Group 2 – Angle Adjustment Kit					
Item #	Description	Lbs.	List		
610702	Manual Angle Adjustment Kit	6	203.00		
610703	Hydraulic Angle Adjustment Kit. Includes cylinder, hoses less tips.		637.00		
	For use on tractor mounted 3-pt units.				

	Optional Broom Accessories				
	Hydraulic Angle Adjustment Kit with elec. hydraulic solenoid				
610940	control. For skid steer rotary brooms used on units equipped with	55	2,044.00		
	only one set of remotes. Includes cylinder, hoses, valve,				
	& flat-faced couplers. Factory installed.				
	Field Installed Hydraulic Kit				
	Field Installed Hydraulic Angle Adjustment Kit with elec. hydraulic				
610950	solenoid control. For skid steer rotary brooms used on units	55	2,079.00		
	equipped with only one set of remotes. Includes cylinder, hoses,				
	valve, & flat-faced couplers				
	Optional Gauge Wheel kit for Rotary Brooms.				
	Gauge wheels allow the operator to set and maintain proper sweeping height				
610665	Dual Gauge wheel kit for all rotary broom models		616.00		

Electrical Wiring Kits for Skid Steers

To connect our electric / hydraulic solenoid control when installed on our Rotary Brooms (or Power Landscape Rakes) into OEM Skid Steer auxiliary electric controls allowing operating the electric / hydraulic solenoid valve from the operator seat with the buttons on the hand control.

nyura	hydraune solehold varve from the operator seat with the buttons on the hand control.					
2507024	ASV Skid Steer 8 Pin Wiring Kit	2	434.00			
2507026	Bobcat Skid Steer 14 Pin Wiring Kit	2	434.00			
2507027	Case Skid Steer 14 Pin Wiring Kit	2	434.00			
2507024	Caterpillar Skid Steer 8 Pin Wiring Kit	2	434.00			
2507028	Caterpillar Skid Steer 14 Pin Wiring Kit	2	434.00			
TBA	Gehl Skid Steer 14 Pin Wiring Kit	2	TBA			
2507029	JCB Skid Steer 14 Pin Wiring Kit	2	434.00			
2507030	John Deere Skid Steer 14 Pin Wiring Kit	2	434.00			
2507031	Kubota Skid Steer 14 Pin Wiring Kit	2	434.00			
2507027	New Holland Skid Steer 14 Pin Wiring Kit	2	434.00			
TBA	Mustang Skid Steer 14 Pin Wiring Kit		TBA			
2507029	Volo Skid Steer 14 Pin Wiring Kit	2	434.00			
2507031	Wacker Neuson Skid Steer 14 Pin Wiring Kit	2	434.00			

