

Worksaver



SmoothCut™ Stump Grinders

Economical and efficient PTO powered stump grinders make stump removal fast and easy. Operator easily controls the grinder from the comfort of the tractor seat. Surefoot™ stabilizer provides solid footing during operation.

- Tractor models require two pair of remote hydraulic outlets.
- Cutting wheel design provides a smoother cutting action and higher productivity.
- Durable carbide-tipped cutting teeth are economical and easy to replace.
- Maneuverable – goes anywhere a tractor can; gets into tight places.
- Easy to operate – hydraulic controls allow easy operation from the seat of the tractor using existing hydraulic controls.
- Heavy duty bushings w/grease zerks are used at major pivot points for increased reliability and extended service life.
- Standard pressure relief valve for precise control of cutting feed rate.
- Pressure relief valve helps reduce hydraulic oil heat buildup keeping tractor hydraulics cooler.
- Rubber deflector helps control chips and debris during grinding.
- Parking stand for easy storage.



Surefoot™ stabilizer


Stump Grinder Specifications

	SG-26A	SG-36A
Hitch	Cat. I	Cat. I / II
Overall Estimated Length (in/cm)	75 / 191	80 / 230
Drive System Protection	Slip Clutch	Slip Clutch
Gearbox Rating / Ratio	60 HP / 1:1.5	100 HP / 1:1.46
Cutting Wheel Construction	Welded 2-piece Laminated Steel	
Cutting Wheel Thickness (in/cm)	3/4 / 1.91	7/8 / 2.22
Cutting Wheel Diameter (in/cm)	26 / 66	36 / 91
Cutting Wheel Speed	810 RPM	788 RPM
@ 540 PTO RPM	5,515 ft. / min.	7,430 ft. / min.
Number of Teeth	33	42
Cutting Teeth Construction	Carbide Steel Bolt-in	
Cut Height Above Ground (in/cm)	18 / 46	18 / 46
Cut Depth Below Ground (in/cm)	10 / 25	15 / 38
Maximum Horizontal Cut (in/cm)	28 / 71	33 / 84
Swing Arc	45°	45°
Minimum Power / Flow Required	22-PTO HP	45-PTO HP
Maximum Power / Flow	50-PTO HP	100-PTO HP
Driveline	PTO / Series 5	PTO / Series 6
PTO Speed	540 RPM	540 RPM
Weight (lbs/kg)	660 / 299	880 / 399
Product No.	812200	812210



WARNING: Read and understand the operator's manual before operation. Stump grinder will put a heavy load on the rear of your tractor. Be sure your tractor is properly counterbalanced. Damage to equipment or personal injury could occur. Never allow children or bystanders around tractor or stump grinder while operating.

Land Management Attachments

Product	Model	Item #	Description	Lbs.	List
Designed for Use on Tractor 3-pt Hitch					
SmoothCut Stump Grinders					
	SG-26A	812200	3-pt mounted PTO driven SmoothCut stump grinder. Features 26" dia. Cutting wheel, carbide steel bolt in teeth. Includes parking stand. Designed for tractors 22- 50 hp. Cat. I Quick Hitch compatible	660	8,533.00
	SG - 36A	812210	Same features as above. Larger 36" dia. cutting wheel. Designed for tractors 45-100 hp. Cat. I/II Quick Hitch compatible	880	9,793.00
Replacement Teeth		811600	Box of 12 Carbide teeth for SG-26 / SG-36, with bolts & washers	2	336.00